



# Anthony Locations

Anthony is a manufacturer and solutions provider of glass doors, lighting systems, and display equipment for use in commercial refrigeration systems. For more information on Anthony, please visit [www.anthonynintl.com](http://www.anthonynintl.com).

## North America Locations

### Sylmar, CA

#### Corporate Offices

12391 Montero Avenue

Sylmar, CA 91342

Phone: 818.365.9451

Toll-Free US: 800.772.0900

Canada: 800.336.8825

Fax: 818.365.2441

### Madison, GA

1101 Sovis Rd

Madison, GA 30650

Phone: 706.342.9300

Fax: 706.342.9303

For Replacement parts go to [www.anthonystore.com](http://www.anthonystore.com)

For our latest instructional and informative videos visit our  channel

For the latest news and upcoming product releases follow us on these social media platforms:



TWITTER



YOUTUBE



LINKEDIN

## Applicable Walk-In Models

<b>Infinity 90 Series</b>	21ZN
---------------------------	------

## Applicable Pass-Thru Models

<b>Infinity 90 Series</b>	23ZN
---------------------------	------

Copyright © 2022 Anthony, Inc. Anthony Company All rights reserved. Information in this document is subject to change without notice. No part of this document may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without permission of Anthony, Inc. All product and company names are trademarks™ or registered® trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them unless otherwise specified.

Anthony products identified in this manual are designed and certified to meet  or  for safety, and  for sanitation standards.

European products meet  requirements.

Each customer is responsible for final site approval.

# Table of Contents

APPLICABLE WALK-IN MODELS .....	2
APPLICABLE PASS-THRU MODELS .....	2
<b>INTRODUCTION.....</b>	<b>7</b>
PROPER USE OF ANTHONY PRODUCTS.....	7
QUALIFIED PERSONNEL .....	7
<b>SECTION 1 - SAFETY.....</b>	<b>8</b>
SAFETY MESSAGES .....	8
SIGNAL WORDS .....	8
SAFETY COLORS .....	8
SAFETY ALERTS SYMBOLS.....	9
USER SAFETY .....	10
General Safety Rules .....	10
Safety equipment – Personal Protective Equipment .....	10
Electrical Connections.....	10
Precautions before work.....	10
EQUIPMENT LIST & TOOLS.....	11
INSTALLATION TIPS .....	11
<b>SECTION 2 – STANDARD WALK-IN LINE-UP FRAME INSTALLATION .....</b>	<b>12</b>
TOOLS REQUIRED.....	12
FRAME UNPACKING.....	12
Figure 2.1: Frame Crate.....	12
FRAME HANDLING DURING INSTALLATION .....	13
Figure 2.2: Clamps to insert Frame into Net Opening.....	13
Figure 2.3: Mullions Attention Label.....	13
Other Frame Installation Recommendations & Suggestions .....	14
NET OPENING & FRAME INSTALLATION.....	15
Figure 2.4: Frame Alignment, Squareness, and Plumb .....	16
SHIMMING THE FRAME .....	17
Figure 2.5: Frame Shimming and Sealing Details .....	18
PROPERLY SEALING THE FRAME .....	19
CONTINUOUS LINEUP FRAME INSTALLATION.....	20
Two (2) Frame Section Line-up .....	20
Figure 2.6: T-Trim installation .....	21
Three (3) or more Frame Sections Line-up.....	21
Figure 2.6: Continuous frame sections layout.....	22
Figure 2.7: T-Trim installation .....	22
Figure 2.8: Last Frame installation .....	23
Figure 2.9: Second to Last Frame installation .....	23
FRAME ELECTRICAL WIRING CONNECTIONS.....	24
Conduit Exit Location .....	24
Figure 2.10: Conduit Exit location .....	24
Figure 2.11: Wiring Labels .....	25
Figure 2.12: Wiring Diagrams .....	25
<b>SECTION 3 – DOOR UNPACKING INSTRUCTIONS.....</b>	<b>26</b>
Figure 3.1. Shipping Crate containing Anthony Doors .....	27
OPENING SHIPPING CRATE.....	27
Figure 3.2. Unscrewing the top portion of the Shipping Crate.....	28
Figure 3.3. Removing the top portion of the Shipping Crate .....	29
Figure 3.4. Offsetting crate weight for removing doors from the crate.....	29
Figure 3.5. Removing Front side of Shipping Crate .....	30
REMOVING DOORS FROM SHIPPING CRATE.....	31
Figure 3.6. Removing Door from Shipping Crate Correctly .....	31

<b>SECTION 4 – DOOR INSTALLATION .....</b>	<b>32</b>
<b>Door HANDLING .....</b>	32
<b>Door INSTALLATION .....</b>	32
Figure 4.1: Seating <b>Door</b> onto Torque Master .....	33
Figure 4.2: Dielectric Grease in SOCKET (hinge pin plug) receptacle .....	34
Figure 4.3: Engage Hinge Pin to Frame .....	35
Figure 4.4: Secure hold-open mounting screw .....	35
<b>TORQUE MASTER™ AND SAG ADJUSTMENT .....</b>	37
Figure 4.5: Torque Master™ .....	37
Sag Adjustment .....	37
Torque Adjustment: .....	38
After Installation <b>Gasket</b> Check .....	39
Figure 4.6: Checking <b>Door</b> Gaskets .....	39
Clean up Work Area .....	39
Check <b>door</b> for Functionality .....	39
<b>SECTION 5 - REQUIRED FUNCTIONALITY FOR COMPLETE INSTALL.....</b>	<b>40</b>
<b>Door</b> Frame Assembly .....	40
<b>Gasket</b> .....	40
Hinge Pin .....	40
Hold Open Assembly .....	40
Torque Master Assembly .....	40
<b>SECTION 6 - COOLER/FREEZER* STORE CONDITION REQUIREMENTS.....</b>	<b>41</b>
Table 6.1: Operating conditions .....	41
<b>OPERATING REQUIREMENTS AND RECOMMENDATIONS FOR OPTIMAL PERFORMANCE .....</b>	41
Figure 6.1 Product Stocking – Shelves required to be fully stocked .....	42
Figure 6.2 Evaporator Air Deflector - Contact evaporator manufacturer for recommended air deflector.....	42
<b>SECTION 7 - ROUTINE PREVENTATIVE MAINTENANCE .....</b>	<b>43</b>
<b>RECOMMENDED MAINTENANCE INSPECTION AND CLEANING INTERVALS.....</b>	44
<b>MAINTENANCE RECOMMENDATIONS.....</b>	44
• Freezer/Cooler Temp & Defrost Settings.....	44
• Frame & Door .....	44
• Door/Frame Hinging Pin & Receptacle Area.....	44
• TorqueMaster™ .....	45
• Gaskets .....	45
<b>CLEANING ROUTINE.....</b>	45
<b>SECTION 8 - TROUBLESHOOTING .....</b>	<b>46</b>
Table 8.1: Installation Troubleshooting .....	46
Table 8.2: General Troubleshooting.....	47
<b>SECTION 9 – FRAME REPLACEMENT PARTS .....</b>	<b>48</b>
Figure 9.1 Frame Assembly for Infinity 90 Series Normal and Low Temperature for Replacement Parts .....	48
Table 9.1 Frame Assembly for Infinity 90 Series Normal and Low Temperature for Replacement Parts List .....	49
<b>SECTION 10 – DOOR REPLACEMENT PARTS .....</b>	<b>50</b>
Figure 10.1 <b>Door</b> Assembly for Infinity 90 Series <b>Door</b> , for Replacement Parts.....	50
Table 10.1 <b>Door</b> Assembly for Infinity 90 Series Replacement Parts List .....	51
<b>SECTION 12 – OPTIMAX 7 LED LIGHTING FIXTURE REPLACEMENT .....</b>	<b>52</b>
Replacement Part Numbers.....	52
<b>REPLACEMENT INSTRUCTIONS .....</b>	53
End Jams .....	55
<b>SECTION 13 – REMOVING &amp; REPLACING THE TORQUE ROD.....</b>	<b>56</b>
Figure 13.1 Torque Rod location.....	56
Figure 13.2 Removing torque rod from the <b>door</b> .....	57
Figure 13.3 Removing torque rod from the <b>door</b> .....	57
<b>SECTION 14 – REMOVING &amp; REPLACING THE HOLD-OPEN ASSEMBLY.....</b>	<b>58</b>
<b>REMOVING THE HOLD-OPEN ASSEMBLY.....</b>	58
Figure 14.1 Removing hold-open assembly from <b>door</b> .....	58
<b>REPLACING THE HOLD-OPEN ASSEMBLY.....</b>	59
Figure 14.2 Hold-open Assembly .....	59

<b>SECTION 15 – REMOVING &amp; REPLACING THE HINGE PIN.....</b>	<b>60</b>
<b>SECTION 16 - TORQUE MASTER REPLACEMENT .....</b>	<b>63</b>
Figure 16.1: Torque Master Replacement .....	63
<b>SECTION 17 – PASS-THRU FRAME AND DOOR INSTALLATION .....</b>	<b>65</b>
TOOLS REQUIRED.....	65
NET OPENING .....	66
Pre-Installation Recommendations and Tips.....	66
FRAME INSTALLATION .....	67
Figure 17.1: Frame Alignment, Squareness, and Plumb .....	68
SHIMMING THE FRAME .....	69
Figure 17.2: Frame Shimming and Sealing Details .....	70
SEALING THE FRAME.....	71
Figure 17.3: Sealing Threshold .....	71
To Install a Pass-Thru Frame with Threshold .....	72
Figure 17.4: Mounting Holes.....	72
For Cut Threshold.....	73
Figure 17.5: Frame Without Threshold .....	73
FRAME ELECTRICAL WIRING CONNECTIONS.....	74
Conduit Exit Location .....	74
Figure 17.6: Conduit Exit location .....	74
Figure 17.7: Wiring Labels .....	75
Figure 17.8: Wiring Diagram .....	76
<b>SECTION 18 – PASS-THRU DOOR INSTALLATION .....</b>	<b>77</b>
Figure 18.1: Inserting door Torque Rod into TorqueMaster .....	77
Figure 18.2: Dielectric Grease in SOCKET (hinge pin plug) receptacle .....	78
Figure 18.3: Connect Hinge Pin .....	78
Figure 18.4: Tighten Hold-Open Screw .....	79
To Remove the Door Assembly.....	80
Figure 18.5: Release TorqueMaster Tension.....	80
Figure 18.6: Remove Hold-Open .....	80
Figure 18.7: Disengage Hinge Pin .....	81
Figure 18.8: Withdraw Away from Hinge Gib.....	81
Figure 18.9: Withdraw from Frame.....	81
Hold Open .....	82
Figure 18.10: Hold Open .....	82
<b>SECTION 19 – PASS-THRU FRAME REPLACEMENT PARTS .....</b>	<b>83</b>
Figure 19.1 Frame Assembly for Infinity 90 Series NT Pass-Thru; Replacement Parts.....	83
Table 19.1 Frame Assembly for Infinity 90 Series NT Pass-Thru Door Replacement Parts List .....	84
<b>SECTION 20 – PASS-THRU DOOR REPLACEMENT PARTS.....</b>	<b>85</b>
Figure 20.1 Door Assembly for Infinity 90 Series NT Pass-Thru; Replacement Parts .....	85
Table 20.1 Door Assembly for Infinity 90 Series NT Pass-Thru Door Replacement Parts List .....	86
Figure 20.2 Door Assembly for Infinity 90 Series NT Pass-Thru; Replacement Parts .....	87
<b>APPENDIX A - GASKET REPLACEMENT GUIDELINES.....</b>	<b>88</b>
PRELIMINARY CONSIDERATIONS FOR SERVICING GASKETS .....	88
Tools Required .....	88
Recommendations and Suggestions .....	88
ORDERING REPLACEMENT GASKETS .....	88
GASKET REMOVAL.....	89
GASKET INSTALLATION .....	90
<b>APPENDIX B – DOOR REVERSAL.....</b>	<b>93</b>
Frame.....	93
Door95 .....	93
<b>APPENDIX C – ANTI-FOG MAINTENANCE .....</b>	<b>96</b>
Care and Cleaning .....	96
<b>APPENDIX D – POM LOCK INSTALLATION .....</b>	<b>97</b>
Figure D.1: Pom Lock Specifications.....	97
STANDARD POM LOCK .....	98
Figure D.2: Plug Removal .....	98
Figure D.3: Hinge Pin Access Plate (lock retainer).....	98
Figure D.4: Front View POM Lock .....	99

<b>APPENDIX E – POM LOCK RETROFITTING.....</b>	<b>100</b>
Figure E.1: POM Lock Retrofit Kit.....	100
Figure E.2: Template Offset location.....	101
Figure E.3: Template Placement on Frame Side view .....	102
Figure E.3: Access Plate Assembly.....	102
Figure E.4: Front View POM Lock.....	103
<b>APPENDIX G – CYLINDER LOCK REPLACEMENT .....</b>	<b>104</b>
Figure G.1: Cylinder lock strike location.....	104
Figure G.2: Cylinder lock exploded view .....	105
Figure G.3: Lock Screw removal .....	105
Figure G.4: Lock cylinder assembly removal .....	106
Figure G.5: Strike Plate replacement .....	106
Figure G.6: Cylinder lock assembly replacement .....	107
Figure G.7: Secure Lock.....	107
<b>APPENDIX I – PASS-THRU DOOR BOTTOM WIPER ADJUSTMENT &amp; REPLACEMENT.....</b>	<b>108</b>
Bottom Wiper Adjustment:.....	108
Figure I.1 – Wiper Adjustment .....	108
Bottom Wiper Replacement: .....	109
<b>APPENDIX J – REMOVING &amp; REPLACING DOOR RAIL PLASTIC COVER.....</b>	<b>110</b>
Tools Required .....	110
Removing Plastic Cover .....	110
Figure J.1 – Plastic Cover corner miter .....	110
Figure J.2 – Prying Plastic Cover .....	111
Figure J.3 – Separating Plastic Cover from the door rail .....	111
Installing New Plastic Cover .....	112
Figure J.4 – Installing replacement Plastic Cover .....	112
Figure J.5 – Applying pressure .....	112
<b>APPENDIX K – ANTHONY ENERGY CONTROLLER.....</b>	<b>114</b>
Features .....	114
Location .....	114
Figure K.1: 4-Door Frame Layout Example for Energy Controller and Sensor Locations .....	114
PROGRAMMING, SETTINGS, AND PARAMETERS .....	115
Sensor Button .....	115
Figure K.2: Energy Controller (Dew Point Sensor).....	115
SETTINGS 115	
Offset Status Indicator Mode.....	115
24-Hour Heat Mode .....	116
Offset Setting Options.....	116
TROUBLESHOOTING .....	117
REPLACEMENT PART NUMBERS.....	117
REPLACEMENT INSTRUCTIONS .....	117
<b>REVISION HISTORY.....</b>	<b>120</b>

---

## Introduction

This manual provides information required to perform installation, repairs, and required maintenance to the Anthony Frames and Doors. This manual is intended as a written guide for personnel who are properly trained and qualified to safely use a variety of different equipment and tools required during the installation, repairs, and performing maintenance of the Anthony Frames and Doors.

All personnel/contractors assigned to install Anthony Frame and/or Doors must read this manual in its entirety as one of the steps in being certified to install and work on Anthony doors. Failure to read and thoroughly understand the material contained in this manual may ultimately result in damage to the equipment, and injury to personnel, and could void the warranty.

The components and systems described in this manual may be operated only by personnel qualified for the specific task by the relevant documentation, warning notices, and safety instructions. Qualified personnel are those who, based on their training and experience can identify risks and avoid potential hazards when working with these types of components and systems.

## Proper use of Anthony Products

Anthony's products may only be used for the applications described in the catalog and the relevant technical documentation. If products and components from other manufacturers are used, these must be recommended or approved by Anthony. Proper transport, storage, installation, assembly, commissioning, operation, and maintenance are required to ensure that the products operate safely and without any problems. The permissible ambient conditions must be complied with.

Anthony has reviewed the contents of this publication to ensure consistency with the hardware and/or software described. Since variance cannot be precluded entirely, we cannot guarantee full consistency. However, the information in this publication is reviewed regularly and any necessary corrections will be included in subsequent editions. Specifications and information are subject to change without notice.


## Qualified Personnel

The Anthony product/systems described in this installation manual should only be operated only by personnel qualified for the specific task following the relevant documentation warning notices and safety instructions. Qualified personnel who, based on their training and experience, can identify risks, and avoid potential hazards when working with these Anthony products/systems.

# Section 1 - Safety

## Safety Messages

This manual includes general, task-specific, and important Safety Messages. Each Safety Message includes several elements, Signal Words, Safety Alert Symbols, Safety Colors, and Safety Message. The following is an example of a safety message with all elements included.



These Safety Messages are defined by the level of severity and are found throughout the manual indicating measures that must be taken while performing the specific task at hand.

## Signal Words

- **DANGER:** Indicates a hazard that, if not avoided, **WILL** result in death or serious injury.
- **WARNING:** Indicates a hazard which, if not avoided, **COULD** result in death or serious injury.
- **CAUTION:** Indicates a hazard that, if not avoided, **WILL** result in minor or moderate injury.
- **NOTICE:** Indicates a hazard or practice that, if not avoided, **CAN** result in equipment or property damage.
- **SAFETY INSTRUCTIONS:** Indicates safety-related instructions, procedures, or the locations of safety equipment.

## Safety Colors

COLOR	SAMPLE	
RED		DANGER
ORANGE		WARNING
YELLOW		CAUTION
BLUE		NOTICE
GREEN		SAFETY INSTRUCTIONS
GREY		ASSEMBLY, MAINTENANCE OR SERVICE ALERT

## Safety Alerts Symbols

Your safety and the safety of others are very important. The following Safety Alert Symbols will be used in conjunction with the Safety Messages to warn of potential risks when installing or maintaining your Anthony Door. These Safety Alert Symbols communicate hazardous information quickly and reinforce the Safety Message without the use of words and across language barriers. These safety messages alert you to potential hazards that could hurt you or others or render damage to Anthony's products. Each safety message is associated with a safety alert symbol. These symbols are found throughout the manual. The definition of these symbols is described below:



*Protective Eyewear— Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.*



*Protective Footwear— Potential risk of injury to your feet, protective footwear is required when performing this and any other associated tasks.*



*Protective Gloves— Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.*



*Hearing Protection— Potential risk of injury to your ears, protective ear coverings required when performing this, and any other associated tasks.*



*Safety Vest— Wearing a high visibility vest is required when performing this and any other associated tasks.*



*Long Pants— Wearing long pants is required when performing this and any other associated tasks.*



*Read Instructions symbol— Read and understand the manual and all other safety instructions before proceeding.*



*Stop – Before you begin: Installation of this assembly requires a person familiar with the construction and operation of electrical systems and the Hazards involved. Read instructions completely and carefully.*



*Risk of Electrical Shock— Potential risk of Electrical Shock; pay close attention to instructions when performing this and any other associated tasks.*



*Commercial Refrigeration – This symbol indicates for use inside a commercial refrigeration case with packaged foods only.*



*Warning – To reduce the risk of fire, electrical shock or injury observe the following:*

- Use this unit in the manner intended by the manufacturer.
- Turn the power off before removing the existing lighting system and follow appropriate lockout/tag-out safety procedures



*Heavy object symbol— Single person lift could cause muscle strain or back injury. Get help when moving or lifting. Use other proper lifting aids, seek assistance, and always use proper lifting techniques when moving.*



*Note – This will contain information that is helpful for a procedure, condition, or operation. Read instructions completely and carefully.*



*Handle with care symbol— Indicates that specific items require care when handling.*



*Pinch Hands symbol – Potential risk of hands sustaining an injury in pinching points.*

## User Safety

### General Safety Rules

These safety rules apply:

- Always keep the work area clean.
- Pay attention to the risks presented by obstacles or other people in the work area.
- Avoid all electrical dangers.
- Pay attention to the risks of electric shock or arc flash hazards.
- Always bear in mind the risk of pinching, electrical accidents, and broken glass.
- Always seek assistance from another person when handling frames and doors

### Safety equipment – Personal Protective Equipment

Use safety equipment according to the company, local, and state regulations. Use this safety equipment within the work area when performing any type of work on Anthony Doors:

- Safety goggles
- Protective shoes
- Protective gloves
- Long Pants
- Hearing protection
- First-aid kit
- Other Safety devices

### Electrical Connections

Electrical connections must be made in compliance with all international, national, state, and local regulations. For more information about requirements, see “*Section 2- Frame Electrical Wiring Connections*–” of this manual detailing requirements.

### Precautions before work

Observe these safety precautions before you work on the installation or service of any Anthony product:

- Provide a suitable barrier around the work area; For example, a caution sign/tape, as allowed by the site manager.
- Ensure all safety guards are in place and secure.
- Recognize the site emergency exits, eyewash stations, emergency showers, and toilets.
- Ensure a clear path of retreat.
- Ensure the **door** will not fall over and/or injure people and/or damage property.
- Ensure lifting equipment is in good condition.
- When using a lifting device, safety device, or other equipment seek assistance when needed.
- Ensure the **door** is thoroughly clean.
- Ensure quick access to a first-aid kit.
- Disconnect and lockout power before servicing.

## Equipment List & Tools

The following is a list of all the different equipment, tools, materials, and other things you will need when installing the Anthony 101N Frame and doors.

### Equipment:

- Safe movers
- Dollies
- Ratchet straps
- Clamps
- Pallet Jack
- J-bar
- Broom
- 2" x 4" Studs

### Frame/Door Installation:

- Shims
- Silicone/Butyl
- Caulk gun
- 4' - 6' level
- Rubber/plastic mallet
- Wire stripper/cutter
- Wire nuts
- Tape measure
- Towels / rags

### Tools:



- Voltage tester
- Soldering Iron
- #2 Philips screwdriver
- Flat-head screwdriver
- Needle-nose pliers
- Razor Knife
- Utility knife
- 5/32" Hex Key
- 7/16 & 1/2" wrenches
- Wireless Drill/Driver

### Materials:

- High Viscosity Dielectric grease  
High Viscosity Dielectric grease  
For Harsh Conditions  
(Anthony P/N: 98-25497-0001)
- NSF Approved Food Grade  
Silicone Sealant
- Plywood Shims
- Foam glass cleaner  
(Ammonia Free)
- Black Paint marker

## Installation Tips



- Complete replacement of wire assemblies is recommended whenever required. Splice wires only if necessary, using proper materials: such as electrical tape, wire nuts, flux core solder, and heat shrink.
- Apply liquid soap to rail plastic covers and gaskets upon installation to facilitate insertion into mounting grooves.
- Keep doors and frames clean for product efficiency. This can also help reduce energy consumption and potential health hazards.
- Whenever binding **gasket** or plastic parts use food-grade silicone.
- Always use the correct tool for the job to be performed. This ensures proper installation and minimizes safety risks.
- If there is any doubt about the work to be performed, consult with a certified technician or Anthony's representative.
- Preventative maintenance is recommended to ensure product longevity.

PROTECTIVE GEAR NOTICE	
	<b>Protective Gloves</b> – Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.
	<b>Footwear Protective</b> – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.

## Section 2 – Standard Walk-In Line-Up Frame Installation

### Tools Required

Refer to “Equipment List & Tools” in Section 1 for a complete list of all equipment, tools, materials, and other things needed for installation. If the Frames are not installed upon arrival, they should be protected from the environmental conditions, and ensure storage of the product indoors at a normal room temperature of 75°F or less, do not store outside, weather can damage the frame and cause issues such as plastic deformation.


PROTECTIVE GEAR NOTICE	
	<i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i>
	<i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i>


### Frame Unpacking

Before beginning installation follow the instructions below to unpack the frames for shipping crates safely and effectively.

1. Locate the factory painted instructions on the crate which read “OPEN ON THIS SIDE” (they are painted with red ink).
2. Carefully, place the crate flat on the floor with the “OPEN ON THIS SIDE” facing up.
3. Remove all screws from the top and bottom wood planks to remove, followed by the center plank.
4. Carefully, pull the frame from the crate and prepare to install it in the case.

**Figure 2.1: Frame Crate**



NOTICE	
	<i>Note – When you have multiple frames, please refer to the “Continuous Lineup Frame Installation” instructions in this section. Depending on your configuration you will have two (2) to three (3) different frames (Right Flanged, Continuous, and Left Flanged).</i>

## Frame Handling during Installation

During installation take special care not to push on or use mullions to lift the frame. Applying force to mullions may cause damage and affect the frame's optimal performance. If needed, we recommend using either a Sliding or Speed Clamp to align and squeeze the Frame into the net opening (see Figure 2.2). When using clamps ensure to gradually squeeze slowly to prevent the frame from bending or cracking.





PROTECTIVE GEAR NOTICE	
	<i>Protective Eyewear– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</i>
	<i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i>
	<i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i>

Figure 2.2: Clamps to insert Frame into Net Opening



1. Once Frame(s) are completely installed proceed to remove the Yellow Labels from the mullions see Figure 2.3 below.

Figure 2.3: Mullions Attention Label






**Other Frame Installation Recommendations & Suggestions**

1. Complete replacement of wire assemblies is recommended whenever required.
2. Apply liquid soap to rail plastic covers and gaskets upon installation, to facilitate insertion into mounting grooves.
3. Keep doors and frames clean for product efficiency. This can also help reduce energy consumption and potential health hazards.
4. Whenever binding [gasket](#) or plastic parts only use food-grade silicone.
5. Always use the correct tool for the job to be performed. This ensures proper installation and minimizes safety risks.
6. If there is any doubt about the work to be performed, consult with a certified technician or Anthony/Anthony representative.
7. Preventative maintenance is recommended to ensure product longevity.
8. Ensure to have correct replacement screw size, quantity, and type if replacing with non-Anthony or non-Anthony hardware.
9. Do not over tighten screws when installing.

## Net Opening & Frame installation

Read the instructions in this Section completely before installing the frame. Before installing the frame, confirm that the size of the net opening accommodates the finished frame, net opening should be larger by 1/8" than the frame size, there should be a gap of 1/8" on top, 1/8" on the right side, and 1/8" on the left side. If the gap tolerances exceed 3/8", the net opening will have to be enlarged to reduce the gap within 1/8". Also, ensure that there is a minimum of 3-1/2" clearance from floor to top of the bottom sill (opening).

PROTECTIVE GEAR NOTICE	
	<i>Protective Eyewear– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</i>
	<i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i>
	<i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i>

The following instructions will ensure proper frame installation:

1. When installing the frame, **DO NOT** install the Frame directly on Sheetrock, the frame is designed to be installed on Cooler/Refrigeration Cases/Freezer Boxes only.
2. Ensure that the Sealing Frame Flap is fully engaged to, Sill, Header, and Jack Studs creating a seal without any gaps (see Figure 2.4).
3. Make sure to **DO NOT** force the frame if the fit is too tight, doing so may cause you to break the Sealing Frame Flap or tweak the Frame.
4. Insert a mounting screw into a mounting hole in each corner of the frame and tighten each screw until it is approximately a quarter inch from being flush.
5. Check the frame is aligned properly or square.
6. Use a measuring tape to measure diagonally from one corner to the opposite and note the distance.
7. Measure the distance between the remaining two corners.
8. Both measurements should be the same, or within a 1/16" difference.
9. Confirm the frame and frame flanges are vertically and horizontally aligned (plumb) to the wall surface around the net opening.
10. Place a level on the top flange of the header frame to check if it is horizontally aligned.
11. If the top of the header frame sags or bows, correct it as necessary.
12. When the frame is completely aligned, tighten all mounting screws securely until each is flush with the frame surface. **DO NOT** over-tighten the screws, as this can cause the frame to become out of square.
13. Check the entire frame to ensure installation is correct. If needed see refer to the "Shimming Frame" section for instructions on how to use shims to align the frame properly.




WARNING	
	<i>Warning: <b>DO NOT</b> over tighten screws onto the frame, as this may cause bowing, sagging, or the frame to become out of square. This will cause installation issues with Door's proper function. Adjusted the frame as needed to ensure it is square and free of bowing and sags.</i>


Figure 2.4: Frame Alignment, Squareness, and Plumb



<b>WARNING</b>	
	<p><i>Warning: Use only food-grade silicone sealant (add caulking for larger gaps) to seal the gap between the frame and the surrounding wall, inside the case, cooler or freezer. Not following these procedures can void Anthony's Service &amp; Warranty on condensation and ice build-up issues.</i></p>

## Shimming the Frame


Shimming is only to be used when necessary and will primarily be done at the header (top) of the frame and opening. If the gap between the frame and net opening is greater than 1/8", proceed to shim the gap for a proper fit. Refer to Figure 2.5, below for a detailed view of Shim location. If everything is aligned, squared, plumb, and gaps do not exceed 1/16" skip the shimming process and proceed to seal the Frame refer to "Sealing the Frame" below for instructions.

PROTECTIVE GEAR NOTICE	
	<i>Protective Eyewear– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</i>
	<i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i>
	<i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i>

The following instructions will ensure to properly shim frame when necessary:

1. Acquire sturdy, penetrable material, such as plywood. The thickness of the material should be wedge-shaped and slightly less than the gap to be filled, remember if the gap is larger than 1/8" opening must be reduced properly to accommodate the frame.
2. When using shims, they must be installed from left to right or top to bottom, **PARALLEL** to frame width or height.
3. Measure the length of the gap (height or width of the frame) and cut the shim material to 1/16 of an inch less than the measured length.
4. Install the shim using the same type of mounting hardware that will be used to install the frame. Be certain that the shim installation hardware will not interfere with the frame installation hardware.
5. If necessary, cut a second shim to the same length and install it on the opposite side of the net opening.
6. If the adjacent sides of the net opening need to be shimmed, repeat the previous steps, matching the shim length to the frame sides of the net opening (less 1/16 of an inch).
7. Shims must **NOT** be used perpendicularly.
8. Excess shim material **MUST** be removed to ensure proper sealing to the frame.
  - A. When the Frame extends past Sill, Header, or Jack Studs ensure that excess shim material does not extend (in-depth, i.e., front to back) past the Sill, Header, or Jack Studs (see Figure 2.5, Example 1 below)
  - B. When Sill, Header, or Jack Studs extend past the Frame ensure that excess shim material does not extend (in-depth, i.e., front to back) past the Frame (see Figure 2.5, Example 2 below)

**Figure 2.5: Frame Shimming and Sealing Details**



## Properly Sealing the Frame

The electrical connection at the Junction Box where the wires enter the frame, and where the wires enter the raceway in the frame must be sealed with NSF Approved Food Grade Silicone Sealant (RTV-108) at the time of installation. Ensure to seal the gap between the frame and the surrounding wall, inside the case, cooler or freezer. Not following these procedures can void Anthony and Anthony's Service & Warranty on condensation and ice build-up issues. Refer to Figure 2.5, on the previous page for clarification.

The following instructions will ensure a proper seal of the Frame:

1. Always ensure that you can locate the Foam insert which lines the entire flange around the Frame; DO NOT remove this foam, it is critical to ensure proper insulation.
2. Ensure that the Sealing Frame Flap is fully engaged to, Sill, Header, and Jack Studs creating a seal without any gaps.
3. Ensure that any excess shimming material is removed as instructed above in "Shimming Frame".
4. If your installation is like Example 1 in Figure 2.5, proceed to seal with Silicone Sealant (RTV-108) as shown.
5. If your installation is like Example 2 in Figure 2.5, proceed to seal with Silicone Sealant (RTV-108) as shown.
6. Follow the manufacturer's curing instructions for the Silicone Sealant (RTV-108) to ensure proper use.
7. Once Silicone Sealant is cured double-check for any remaining gaps that require more sealant.


### WARNING






**Warning:** Ensure to use silicone approved for use in commercial refrigeration applications which meets all requirements and guidelines. Use only food-grade silicone sealant (add caulking for larger gaps) to seal the gap between the frame and the surrounding wall, inside the case, cooler or freezer. Not following these procedures can void Anthony's Service & Warranty on condensation and ice build-up issues.

## Continuous Lineup Frame Installation

Use the following instructions for walk-in line-ups when more than one frame section(s) is required (applies to 101N, 101B & 101T walk-in configurations with more than one frame). These instructions will guide you on how to install multiple frames using the provided T-Trim(s) which seals the gap between any two (2) frames. Whether you have two or more frames use the instructions below to ensure proper installation of the entire frame line-up. When your installation only requires one frame section there is no need for T-Trim installation.

NOTICE	
	<p><i>Note – These instructions apply only to the 101N, 101B, and 101T in both Normal Temperature and Low-Temperature walk-in applications only. For Pass-Thru configurations please refer to “Section 18 – Pass-Thru Door Installation” for instructions on installation (which are limited to 1 and 2 door configurations).</i></p>

PROTECTIVE GEAR NOTICE	
	<p><i>Protective Eyewear– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</i></p>
	<p><i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i></p>
	<p><i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i></p>

### Two (2) Frame Section Line-up

The following instructions are for installations that required **two (2) frame sections only**:

1. To begin, set the first frame (ensure that the first frame has a full flange on the right side and continuous flange on the left side) against the far-right side of the net opening/case opening and install according to instructions previously noted in this section ensuring to square, plumb, secure, and seal the first frame (shim if needed).
2. Ensure the first frame is installed correctly, then set the second frame into the net opening/case opening (ensure that the second frame has a full flange on the left side and a continuous flange on the right side). Slide the second frame to the far left of the net opening/case opening and slide it snug frame against the opening. Ensure to square, plumb, secure, and seal the frame (shim if needed). Use instructions given on previous pages.
3. After installing the second frame insert a T-Trim between the first and second frames.
4. Once T-Trim is in place, insert binding bolts (sex bolts) through the right side of the first frame, and into the left side of the second frame. Tighten until frames are pulled together. Refer to Figure 2.6.

**Figure 2.6: T-Trim installation**




**Three (3) or more Frame Sections Line-up**

The following instructions are for installations that required **three (3) or more** frame sections:


1. To begin, set the first frame (ensure that the first frame has a full flange on the right side and continuous flange on the left side) against the far-right side of the net opening/case opening and install according to instructions previously noted in this section ensuring to square, plumb, secure, and seal the first frame (shim if needed). To continue installing the next frame you will need to install the T-Trim between frames.
2. Ensure the first frame is installed correctly and proceed by placing T-Trim on the left end (continuous flange side) of the first frame, then set the second/next frame into the net opening/case opening (ensure the second frame is a continuous frame with continuous flanges on both ends) and slide it snug frame against the T-Trim and the first frame, ensuring you sandwich the T-trim snugly between the first and second frame. See Figures 2.6 and 2.7.

**Figure 2.6: Continuous frame sections layout**



- Once the first frame, T-Trim, and second frame are in place, insert binding bolts (sex bolts) through the right side of the first frame, and into the left side of the second frame. Tighten until frames are pulled together. Refer to Figure 2.7.


**Figure 2.7: T-Trim installation**



- Once the two frame sections and T-Trim are together and secured, ensure to square, plumb, secure, and seal the second frame (shim if needed). Use instructions given on previous pages.
- Continue repeating Steps 1 and 4 if needed to accommodate numerous frames as needed.
- Once you are ready to install the **second to last frame**, you will need to **STOP** and install the **last frame** before the second to last frame (ensure that the last frame has a full flange on the left side and continuous flange on the right side). Slide the last frame to the far left of the net opening/case opening and slide it snug frame against the opening. Ensure to square, plumb, secure, and seal the frame (shim if needed). Use instructions given on previous pages.
- After installing the last frame proceed to install the second to last frame (ensure the second to last frame is a continuous frame with continuous flanges on both ends) into the net opening/case opening between the two (2) frames (last frame and third to last frame). Ensure to square, plumb, secure, and seal the frame (shim if needed).


Use instructions given on previous pages. Refer to Figure 2.8.

**Figure 2.8: Last Frame installation**



8. After installing the second to last frame Insert a T-Trims on both ends of the second to the last frame and install according to instructions in Step 3. This will ensure the sealing of all installed frames. Refer to Figure 2.9


**Figure 2.9: Second to Last Frame installation**





9. Once all frames and T-Trims have been installed, seal the entire line-up from inside of the case, caulking all four sides of the frame, in between the frame and net opening, and in any gaps left on the back end of the frames caused using the T-Trim(s) that were installed.

## Frame Electrical Wiring Connections

The electrical connection at the Junction Box where the wires enter the frame, and where the wires enter the raceway in the frame must be sealed with silicone caulking at the time of installation.

<b>WARNING</b>	
	<p><b>Stop:</b> Wiring for lights should have a separate circuit from the <i>door</i>/frame heater wiring circuit.</p>

<b>WARNING</b>	
	<p><b>Warning</b> – To reduce the risk of fire, electrical shock or injury observe the following:</p> <ul style="list-style-type: none"> <li>- Use this unit in the manner intended by the manufacturer.</li> <li>- Turn the power off before removing the existing lighting system and follow appropriate lockout/tag-out safety procedures</li> </ul>

<b>WARNING</b>	
	<p><b>Risk of Electrical Shock</b>– Potential risk of Electrical Shock; pay close attention to instructions when performing this and any other associated tasks.</p>


### Conduit Exit Location

For walk-in frames, the conduit exit for connection wires is typically located on the top right inside of the frame. Depending on your needs when ordering you can designate where you would prefer the conduit exit to be located. Frame Junction box location is determined by customers.

**Figure 2.10: Conduit Exit location**



**Figure 2.11: Wiring Labels**




The seven individual wires extending from the flexible conduit atop the frame, provide electrical power to various frame and door functions for the wiring diagram label, affixed to the frame header.

Using wire connectors, these wires should be grouped by the Hotwires (Circuit wires), the Neutral wires, and the ground wire for connection to either the facility or the case power.

- Blue/White wire connects to the supplied Hot (or Lights Circuit Wire).
- White/Blue wire connects to the supplied Light neutral wire.
- Red and Black wires connect to the supplied Hot (or Door/Frame Heater Circuit Wire).
- White/Red and White/Black wires connect to the supplied neutral wire for the Door/Frame Circuit.
- Green/Yellow wire connects to the supplied ground wire.

**Figure 2.12: Wiring Diagrams**



**NOTICE**







*Note – Wiring for lights should have a separate circuit from the door/frame heater wiring circuit.*

## Section 3 – Door Unpacking Instructions

There are several precautions that you must be aware of when staging and unpacking the doors from the crate. The following section will address these precautions.

As always, please read this manual in its entirety. It should answer most of your installation questions. For personal and system safety, and optimum product performance, make sure you thoroughly understand the contents before unpacking, installing, using, or maintaining this product.

PROTECTIVE GEAR NOTICE	
	<i>Protective Eyewear– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</i>
	<i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i>
	<i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i>

WARNING	
	<i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i>



WARNING	
	<i>Warning: When removing doors from crates <b>DO NOT</b> lift or remove the <b>door</b> from handles. Doing so will cause the handles to break off the glass or possibly shatter the entire <b>door</b>! Please use extreme caution and have at minimum two people lift the <b>door</b> one person from each end to ensure proper removal from the crate.</i>

Figure 3.1. Shipping Crate containing Anthony Doors




## Opening Shipping Crate

Anthony takes great care to ensure that your doors arrive undamaged and in acceptable condition shape. Please use and follow these steps to ensure the proper removal of your doors from the shipping crate.


1. When staging for installation, ensure the crate(s) are in an area that is clear of obstructions and has enough clearance to be safely removed from the crate such as furniture, fixtures, toolboxes, etc.
2. Start by using a screwdriver or drill with a Philips screw bit to remove the screws holding the top wooden slats onto the crate (see Figure 3.2. below).


Figure 3.2. Unscrewing the top portion of the Shipping Crate



3. After removing all screws securing the top wooden slats to the crate, remove the wooden slats (see Figure 3.3. next page).

**Figure 3.3. Removing the top portion of the Shipping Crate**



<b>WARNING</b>	
	<p><i>Warning: If you only have one or two people to remove doors from the crate, please see Step # 4; if 3 or more people are available proceed to Step # 5.</i></p>


4. After removing the top wooden slats from the crate, use the same wooden slats or another piece of wood to place under the crate to offset the weight as shown in Figure 3.4. below. Simply use a hand jack or forklift to lift the front side with “Open This Side” marking enough to wedge in a few pieces of wood causing the weight of the crate to shift and insuring when doors are removed the rest will not fall over.

**Figure 3.4. Offsetting crate weight for removing doors from the crate**



5. The next step is to remove the front panel. To do this, unfasten the screws located along with the front side panel (See Figure 3.5. next page). The crate has been labeled with “Open this Side” to ensure you do not open the incorrect side.

Figure 3.5. Removing Front side of Shipping Crate






**WARNING**



*Warning: When removing the front side of the crate ensure that you are opening side the that is labeled "Open This Side". Do not remove any additional crate panels, the doors have specifically been packed to be removed from the side indicated on the crate.*

## Removing Doors from Shipping Crate

PROTECTIVE GEAR NOTICE	
	<i>Protective Eyewear– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</i>
	<i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i>
	<i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i>

Please use and follow these instructions to ensure the proper removal of your doors from the shipping crate.

1. When removing the doors from the crate do not use **door** handles to lift or move the doors.
2. Have one person at each end firmly hold the **door** and lift it upwards to clear protective inserts at the bottom of the crate.
3. While the **Door** is suspended in the air and clear of any obstructions, carefully move away from the crate.
4. If possible, have a third person holding doors in the crate to ensure the remaining doors do not fall over and possibly be damaged. If a third person is not available, please see Step #4 in the previous section “Opening Shipping Crate” to insure safely removing doors with less than 3 people.



WARNING	
	<i>Warning: When removing doors from crates DO NOT lift or remove the <b>door</b> from handles. Doing so will cause the handles to break off the glass or possibly shatter the entire <b>door</b>! If the weight of the crate is not offset as instructed in step#4, make sure to have a third person holding the doors while they are being removed.</i>

Figure 3.6. Removing **Door** from Shipping Crate Correctly







5. Continue to Safely remove all doors from the crate as needed. See Section 4 **Door** Installation on the next page for instructions on how to install the **door** onto the frame properly.

## Section 4 – Door Installation

This section provides the information needed to safely perform the proper installation of Anthony doors onto the frame.

### Door Handling

Once staging is complete and you have removed the first door and made all the Pre-Installation enhancements it is time to begin installing the Anthony Doors one at a time. Moving an Anthony door throughout the store will be difficult due to the weight and size. You must use two (2) technicians, at minimum, to always lift and carry doors.

PROTECTIVE GEAR NOTICE	
	<i>Protective Eyewear– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</i>
	<i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i>
	<i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i>
WARNING	
	<i>Warning: When removing doors from crates DO NOT lift or remove the door from handles. Doing so will cause the handles to break off the glass or possibly shatter the entire door! If the weight of the crate is not offset as instructed in step#4, make sure to have a third person holding the doors while they are being removed.</i>


### Door Installation

The following instructions will guide you through the installation process, please read all instructions in full and understand them entirely before you begin.

Once the current frame has been installed, you can now proceed to install the new doors. Refer to “Equipment List & Tools” in Section 1 for a complete list of all equipment, tools, materials, and other things needed for installation.

- Carefully lift the door with the handle facing forward, begin to adjust, pivot, and align the torque rod end so it aligns to the Torque Master on the base of the frame, while lifting safely insert the torque rod into Torque Master without damaging the door or frame as shown in Figure 4.1.
- You should feel the door drop into place when swinging the door, make sure the Torque rod is fully engaged within the Torque Master before proceeding, failure to do so may result in injury and damage to the Anthony Door.

Figure 4.1: Seating Door onto Torque Master



3. Now we will proceed to engage and lock the hinge pin into place and prepare the SOCKET (hinge pin plug) receptacle by using Dielectric grease on the socket of the frame before inserting the door hinge pin.

- Anthony recommends applying a minimum of three (3) grams per door Hinge Pin receptacle of its High-performance Dielectric Grease (Refer to the specific door model's installation manual for more detailed instructions on how to apply):
  - Anthony P/N: **98-25497-0001** (approximately 100 grams, sufficient for up to 30 door receptacles).
  - Anthony P/N: **98-25497-0002** (approximately 3 gram packet, sufficient for up to 1 door receptacle).


**Figure 4.2: Dielectric Grease in SOCKET (hinge pin plug) receptacle**



- Engage door with hinge pin inserted into SOCKET (hinge pin plug) receptacle at top of the frame. Push the door into the frame until the hinge pin snaps in place. See Figure 4.3.


**Figure 4.3: Engage Hinge Pin to Frame**



<b>WARNING</b>	
	<p><i>Never use anything like a hammer, rubber mallet, or another tool to strike the Hinge pin into the Gib receptacle. Doing this will cause damage to the pin receptacles in the GIB and cause a short. You must only push this into place gently when completely aligned and ensure it is locked into position when done. You will feel it and hear a click when it is engaged properly.</i></p>

- Insert the hold-open bolt through the elongated hold-open slot.
- Insert the hold open through stand-off and secure it with a #2 Phillips screw (provided).
- Keep the screwdriver perpendicular to the screw head. Make sure the tip is fully seated into the screw head recess before turning.

**Figure 4.4: Secure hold-open mounting screw**



**WARNING**



**WARNING: DO NOT use power tools to install and secure the hold-open screw.**

8. Now you will need to set the **door** tension swing and correct the **door** alignment by adjusting the Torque Master™. Refer to “Torque Master™ and Sag Adjustment” for details on proper adjusting.

## Torque Master™ and Sag Adjustment

The TorqueMaster regulates the **door** alignment and the **door** closing tension. For the **door** to operate properly it must be square in the frame and the pivot centerline must be perpendicular to the level. If the frame was correctly installed, the top and bottom gaps between the **door** and frame will be even from the pivot side to the handle side of the **door**. If the gaps are not even, adjust the end screw on the Torque Master as required to make it even. For frames that are not square and level, the sag adjustment should be made with a level on the top or handle edge of the **door** (with it nearly closed). Once the **door** sag is correct, proceed to the torque adjustment.





Figure 4.5: Torque Master™




### Sag Adjustment

1. Adjust the **door** sag to square it in the frame by turning the screw that is marked SAG ADJ. (sag adjustment), on the end of the Torque Master, until the **door** is square in the opening.
  - a. Turn counterclockwise to raise the handle side of the **door**.
  - b. Turn clockwise to lower the handle side of the **door**.

**Torque Adjustment:**

1. Use a flathead screwdriver to adjust the torque rod tension, by turning the outside screw on the TorqueMaster.

<b>WARNING</b>	
	<b>Warning:</b> Exercise caution when handling the <i>door</i> and <i>DO NOT</i> use power tools when adjusting the Torque Master™.

2. Remove tension on torque rod closing force by rotating front TorqueMaster screw CW until *door* closing tension is relieved such that the *door* remains open 1 inch to 3 inches from *gasket* touching the contact plate.
3. Slowly increase the closing torque by rotating the front screw CCW until the *door* just closes (i.e., the magnetic *gasket* attracts the contact plate).
4. Continue to rotate the front screw two (2) additional CCW turns after the *door* closes.
5. The adjustment is completed. To test the adjustment, verify that the *door* closes from any opening distance, and the *door* remains open when the Hold open detent is engaged.

### After Installation Gasket Check

After installation is completed, ensure that all **door** gaskets are securely installed for optimal sealing performance. When handling the **door** during installation gaskets can be pulled out of place.

1. Use your hands and fingers to check the entire perimeter of the **door** and the **gasket**.
2. If any portion of the **gasket** is not correctly in place, press the **gasket** dart firmly back into place into the back plastic of the **door**. As shown in Figure 4.6.
3. Make sure to run your fingers a second time to ensure that the dart of the **gasket** is fully engaged into the groove of the back plastic around the entire **door** parameter. As shown in Figure 4.6.

**Figure 4.6: Checking Door Gaskets**



### Clean up Work Area

After installation is completed, ensure to dispose of any installation-related debris and trash. Remove any crates remaining in the shopping area and/or any barriers set up.

### Check **door** for Functionality

Refer to *"Section 5 - Required Functionality for Complete Install"*

---

## Section 5 - Required Functionality for Complete Install

The following items must be functional for the installation to be completed and closed out:

### Door Frame Assembly

Door/frame assembly should be in proper alignment and level/plumb.

### Gasket

The **gasket** must be properly sealed and touch the contact plate around the entire **door** assembly. The **gasket** must not be rolled or torn. After handling the **door** during installation, the **door** gaskets may be pulled out of the **door** rail dart, to ensure optimal sealing between the **door gasket** and frame you must check that gaskets are properly seated in the **door**. To re-install the gaskets, “**Gasket Check**” section in “*Section 4 – Door Installation*”.

### Hinge Pin

Three (3) grams of a high viscosity dielectric grease must be applied to the Hinge Pin receptacle at the time of installation. For installations where doors are in Harsh and/or Extreme ambient conditions with excessive moisture, it is recommended to use a minimum of 3 grams of Anthony P/N: 98-25497-0001 dielectric grease to fill the holes in the Hinge Pin receptacle socket. This will prevent corrosion and other issues excessive moisture can cause.

### Hold Open Assembly

Hold open bolt must be in good working order, not broken, bent, or stripped. Hold open bracket must be functional and properly hold the **door** in the open position when open completely and engaged.

### Torque Master Assembly

Torque Master assembly must be properly adjusted and functioning to close the **door** when it is held partially open (6 Inch test) When the installer lets go of the handle, the **door** should close completely without any pressure from the installer.


## Section 6 - Cooler/Freezer\* Store Condition Requirements

The installation of Anthony doors in various applications requires specific store conditions to achieve optimal performance. Please note that ambient conditions in your store may vary throughout the day. Anthony/ Anthony Doors are built to in line with ANSI/ASHRAE Standard 72-2014 Test Standard.

*\*Cooler/Freezer refers to either a walk-in cooler or freezer; or an LT or NT refrigerated display case.*

**Table 6.1: Operating conditions**

NORMAL TEMP	
Models	Operating Conditions
21ZN, 21OZ	75°F, 65% RH AMBIENT / 35°F WALK-IN
LOW TEMP	
Models	Operating Conditions
23ZN, 213Z	75°F, 65% RH AMBIENT / -10°F FREEZER

WARNING	
	<p><i>Stop – Cooler/Freezer and store operating conditions that exceed the required limits may cause condensation and result in sweating of doors. Facility operators should monitor the cooler/freezer and store operating conditions regularly to ensure the required conditions are met.</i></p>

### Operating Requirements and Recommendations for Optimal Performance

- Recommend HVAC vents do not blow directly on doors.
- Use of high viscosity dielectric grease is recommended for Hinge Pin Receptacle; for Harsh environments the use of dielectric grease Anthony P/N: 98-25497-0001 is strongly recommended to ensure optimal performance and protect electric connections.
- Cooler/Freezer temperature settings must not operate below the recommended temperatures: Refer to Table 6.1 Operating conditions above.
- Evaporators must be equipped with defrost termination control to end the termination early if the coil is cleared. Recommend scheduling defrost during low traffic periods. Adjust the duration of evaporator defrosts according to the manufacturer’s recommendations.
- The cooler/Freezer must be regularly inspected for air leaks. Identified air leaks must be sealed. Visually inspect box penetrations and adjoining surfaces: the use of a flashlight is helpful. A smoke stick can be used to validate an infiltration while the cooler/freezer is operating.
- Avoid direct evaporator air impingement on the cooler/freezer door. This can be achieved by ensuring shelves are always fully stocked.
- It is strongly recommended that air deflectors be installed in every evaporator inside the walk-in cooler/freezer. Refer to Figures 6.1 and 6.2.

Figure 6.1 Product Stocking – Shelves required to be fully stocked








Figure 6.2 Evaporator Air Deflector - Contact evaporator manufacturer for recommended air deflector.



## Section 7 - Routine Preventative Maintenance

The following provides information needed to safely perform regular periodical preventative maintenance. Regular preventative inspections will maximize the longevity of your Anthony products. These simple tasks will go a long way in ensuring optimal performance. Depending on maintenance being performed you may need to shut down the **door** or kill all power to the doors. Refer to your specific **door** model Installation Manual on how to disengage power. The use frequency of doors will vary from location to location, and the frequency in routine for preventative maintenance will vary for everyone depending on the amount of traffic.

For Anthony products used in harsh or extreme ambient conditions, it is recommended that these inspection intervals be performed on a more regular basis. When issues are found please refer to your specific model's installation and service manual for detailed information on how to replace and re-order needed parts or contact your Anthony representative.

<b>PROTECTIVE GEAR NOTICE</b>	
	<i>Protective Eyewear– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</i>
	<i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i>
	<i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i>

## Recommended Maintenance Inspection and Cleaning Intervals

Action	Store Conditions	Description
Preventative Inspection	Normal Conditions	Once each quarter (every 3 months)
	Harsh Conditions	Once a month (every 30 days)
Cleaning	All Conditions	Once a month (every 30 days)

*Note: These are recommendations based on historical data of other Anthony door products and can vary depending on location, store conditions, store traffic, and other unknown variables.*

## Maintenance Recommendations

Here is an outline of standard recommend inspection interval recommendations:


- **Freezer/Cooler Temp & Defrost Settings** – Regularly inspect and ensure that ambient conditions are correct, refer to the values that pertain to your specific Door Model for Operating Condition values that are required for optimal door performance, and to maximize door and frame longevity.
- **Frame & Door** – Regularly ensure to check for wear/tear on frame and door this can include:
  - Ensuring that warning labels and product identification labels are all intact
  - Ensure all Bezels are intact and not damaged
  - Ensure that Vents are clean and allow maximum Airflow
  - Ensure all plastic backs are secured and undamaged
  - Handles are secured to the door
  - Ensure the door is opening to the angle of 87°
  - Rails are intact, not broken, and securely in place
- **Door/Frame Hinging Pin & Receptacle Area** – Regularly ensure to check for wear/tear all hinging parts include:
  - Inspect that the Hinge Pin is properly connected with the frame receptacle, **DO NOT** remove the factory installed dielectric grease from the Hinge Pin assembly to ensure the proper function
  - Inspect that the Hinge Pin and receptacle are rust/corrosion free, and there is an adequate amount of Dielectric Grease present
  - If when replacing or servicing Door and it is removed from the Hinge Pin receptacle, ensure to re-apply dielectric grease before installation of the door
  - Anthony recommends applying a minimum of three (3) grams per door Hinge Pin receptacle of its High-performance Dielectric Grease (Refer to the specific door model's installation manual for more detailed instructions on how to apply):
    - Anthony P/N: **98-25497-0001** (approximately 100 grams, sufficient for up to 30 door receptacles).
    - Anthony P/N: **98-25497-0002** (approximately 3 gram packet, sufficient for up to 1 door receptacle).
  - Replace any broken or damaged Hinge Pin and ensure to apply an adequate amount of Dielectric Grease
  - Visually and mechanically Inspect Hold-Open Arm, Screw, and Spacer for wear/tear/damage and that Screw it is secure

- **TorqueMaster™** – To check the TorqueMaster™ is functioning correctly open each **door** and ensure that the tension makes the **door** close smoothly and gently on its own. If the **door** closes either too slowly or rapidly the issue can be fixed by adjusting that Torque Master™ refer to the “Torque Master™ and Sag Adjustment” section for details. If after adjusting the issue is still present the next step is to replace the Torque Master™, refer to this manual for detailed instructions on replacing. If the opening and closing of **door** is still an issue after replacing the Torque Master™ you may need to replace the Torque rod. See Section 13 om detailed instructions on how to achieve this.
- **Gaskets** – When inspecting gaskets ensure that they are sealing properly along the entire perimeter of the **door**. Also, ensure that the **gasket** is properly inserted into the **door** plastic grove. Inspect and ensure gaskets are free of cracks, tears, deformities, and hardening.

## Cleaning Routine

List of Items that should be cleaned during the monthly cleaning routine:

- **General Cleaning** – Regularly clean by wiping down the frame, **door** rails, bezels, and gaskets by checking for food debris, dust, and other foreign objects that may prevent the **door** from closing correctly. Use non-abrasive cleaning apparatus (i.e., microfiber cloth) when wiping down frame and **door** rails.
- **Cleaning Inside Door Glass\***: To clean **door** glass on the inside of the **door**. We recommend the following cleaners:
  - Windex® Original
  - Windex® Vinegar
  - Fantastik®
  - Formula 409®
  - MicroClean Professional APC®

NOTICE	
	<p><i>Note – any cleaner used or listed here MUST be Ammonia Free. Only use cleaners on the glass portion of the <b>door</b>. Using harsh chemicals on PVC or ABS plastic portions of the <b>door</b> may damage the material.</i></p>

Fantastik® and Windex® are registered trademarks of S.C. Johnson & Son, Inc. | Formula 409® are registered trademarks of The Clorox Company. | MicroClean Professional APC® (formerly Now® all-purpose cleaner) is a registered trademark of The Mirachem Corporation.

## Section 8 - Troubleshooting

**Table 8.1: Installation Troubleshooting**

PROBLEM / ISSUE	PROBABLE CAUSES / FIXES	FINAL REMEDY
Condensation on <b>Door</b> Glass, <b>Door</b> Rail, or Frame	Fan to <b>Door</b> Proximity too small	Install air deflector
	Evaporator fans blowing cold air directly onto glass/frames	
	Shelves not fully stocked	Stock merchandise
	<b>Door/gasket</b> seal malfunction	See "Insulation or Air Leaks"
	Store conditions (temperature and relative humidity) outside required parameters	Adjust HVAC / Dehumidifier settings to meet required parameters
	Cooler/freezer temperature set too low	Adjust cooler/freezer temperature to design specified setting
	Check Store conditions	Confirm the room temperature in Normal temp is 75° F and the humidity is below 65%RH and the walk-in case is in the range of 35° F, on Low temp the temperature must be 75° F and the humidity is below 65%RH and the walk-in case is in the range of -10° F
Condensation in between Glass Panes	Seal compromised cause loss of gas or vacuum (check by cleaning the glass on merchandise and customer sides)	Replace <b>door</b>
Rust/Corrosion on Hinge Pin	Excessive moisture from ambient/store conditions	Add Dielectric Grease to Hinge Pin Receptacle Replace the Hinge Pin/ add an adequate amount of Dielectric Grease
Ice buildup inside Freezer	Air infiltration Box/frame not sealed according to Anthony's instructions	See "Insulation or Air Leaks"
<b>Door</b> not closing or sealing	Check <b>gasket</b> to ensure proper installation	Replace <b>gasket</b>
	Check the <b>gasket</b> for damage	
	Check Hold-Open	Replace Hold-Open
	Check TorqueMaster torque (plumb)	Replace TorqueMaster2
	Check TorqueMaster sag	
	Check Frame/ <b>Door</b> is square	
	Check Plastic covers on rails	Replace Plastic Covers
Check Plastic covers on frame mullions		
No Power to Frame	Check Power Supply	Adjust energy controller to Full-On Replace Power Supply Replace Energy/Humidity Controller Replace Hinge Pin Replace wiring
	Check energy/humidity controller	
	Check hinge pin connections	
	Check glass wire connections	
	Check hinge pin wiring	
	Check Power connections	
Low Voltage	Check main voltage	Adjust energy controller to Full-On Replace Frame heater wires
	Check humidity controller	
	Check the Amp draws to the heater wires in the frame	
<b>Door/Gasket</b> Seal - Malfunction	Check <b>gasket</b>	Replace <b>gasket</b>
	Check <b>door</b> mount	Replace hinge pin
	Check <b>Door</b> is square and level	Replace TorqueMaster
Frame not Square or Plumb	Frame not properly shimmed	Use correct Shim to level frame
	The frame should be square to within 1/16"	Use a rubber mallet to adjust the frame plumb within 1/16"
	The frame should be plumb within 1/16"	
Insulation or Air Leaks	Frame must be properly shimmed, level, and plumb	Seal gaps with approved NSF-approved Food Grade Silicone Sealant per Quick Installation Requirements Guide. Check Gaskets are sealing properly for all <b>door</b> openings
	Use RTV-108 NSF Approved Silicone Caulk to fill the perimeter of the frame on the refrigeration side (inside the case) and at all frame joints as required so there are no air gaps.	
	Use RTV-108 NSF Approved Silicone Caulk to fill the perimeter of the frame on the refrigeration side (outside the case) and at all frame joints as required so there are no air gaps.	
	Ensure Gap between frame and refrigeration does not exceed 1/8", gaps larger than 1/8" will require additional shimming to reduce gap size before sealing	
	Ensure all electrical conduits are properly sealed to prevent moisture and air from migrating into the box, use RTV-108 NSF Approved Silicone Caulking if necessary	

**Table 8.2: General Troubleshooting**


PROBLEM / ISSUE	PROBABLE CAUSES / FIXES	FINAL REMEDY
Glass condensation	No Power	Check power supply Check humidity controller Check Hinge Pin connections Check glass wire connections Check Hinge Pin wiring
	Low voltage	Check main voltage Check humidity controller
Door/Frame Rail Condensation	No Power	Check power supply Check humidity controller Check hinge pin connections Check <b>door</b> wire connections Check frame wire connections
	Low voltage	Check main voltage Check humidity controller hinge pin
	<b>Door</b> seal malfunction	Check <b>gasket</b> Check <b>door</b> mount wiring
<b>Door</b> not closing or sealing	<b>Gasket</b> malfunction	Check <b>gasket</b> installation Check the <b>gasket</b> for damage Replace <b>gasket</b>
	<b>Door</b> not closing properly	Check hold-open Check TorqueMaster torque Check TorqueMaster mount Adjust TorqueMaster sag Check frame/ <b>door</b> square Check plastic covers on rails
<b>Door</b> saw-toothed	<b>Door</b> or frame not square	Square <b>door</b> to 1/16" Adjust TorqueMaster sag Replace worn hinge pin socket Facility or case not level Frame not properly shimmed Hold-open binding/damaged
LED Fixture inoperative	Power switch OFF	Turn the power switch ON
	LED burned-out	Replace LED Fixture
	LED failure	Check socket mounting Check socket/lamp connection Check ground wire connection Replace LED Fixture
	Incorrect LED fixture	Replace with the correct LED fixture
	LED Driver failure	Check wire connections Replace LED Driver
	Incorrect wiring	Check ground wire connection Reconfigure wiring Replace wiring
LED intermittent or dimming	Defective wiring	Check & replace wiring
	Defective LED Fixture	Replace LED Fixture

## Section 9 – Frame Replacement Parts

The following section list Frame Replacement parts for both Normal Temperature and Low-Temperature Frames.

**Figure 9.1 Frame Assembly for Infinity 90 Series Normal and Low Temperature for Replacement Parts**

(See Table 9.1 for Part Numbers)



**NOTICE**



*Note: Parts depicted in Red can be replaced, parts in Black are not replaceable. Mullions shown detached from frame assembly only for clarity; Mullions are not replaceable or meant to be removed.*

**Table 9.1 Frame Assembly for Infinity 90 Series Normal and Low Temperature for Replacement Parts List**

ITEM NO.	PART NUMBER	DESCRIPTION
1	02-10568-000X	ASSEMBLY, TORQUE MASTER
4	02-24974-02275 <sup>1</sup>	ASSEMBLY, CONTACT PLATE, NO LCK, NO DVR, NO DR HT, NT
5	02-24974-12275 <sup>1</sup>	ASSEMBLY, CONTACT PLATE, NO LCK, DVR, NO DR HT, NT
6	<a href="#">11-10602-0001</a>	BRACKET, POST, MULLION, CTR,101X
7	11-22496-5001	PLATE LATCH, 210Z
8	11-25088-000X	BRACKET, POST, END
9	15-12520-20330 <sup>1</sup>	PLATE, CONTACT, END-TO-MULLION, 1.984X27.60
10	15-12520-20375 <sup>1</sup>	PLATE, CONTACT, JAMB
11	15-12520-20430 <sup>1</sup>	PLATE, CONTACT, MULLION-TO-MULLION, 1.984X28.06
12	<a href="#">20-11314-0001</a>	PLUG, DUMMY, DR, REVERSIBLE
13	20-11935-000X	CLIP, SPRING
14	<a href="#">20-12754-0001</a>	CAP, PLUG, TORQUE MASTER
15	20-15819-0001	PLUG, TRUSS
16	20-24915-1023	EXT, RETAINER, FRAME & MULLION, 101N
17	40-10993-3014	SCREW, #8 X 1-3/4, PHD, SMS, TPAB, BLACK
18	40-10994-1005	SCREW, 8-32 X 1/2, PFH, TYPF, ZINC
19	40-11114-1011	SCREW, #8 SMS TYP B, PPH
20	40-12514-3010	SCREW, 6 X 7/8 SMS TYP B, PFH, BLACK, ZC
21	<a href="#">40-12665-3003</a>	SCREW, 6-32 X 1/4, PPH, TPII, BLK ZC
22	40-13723-1006	SCREW, 10-24 X 7/16, TAP, 1/4", ZN
23	<a href="#">40-14616-0001</a>	STANDOFF, PIVOT, HOLD OPEN
24	40-25072-1005	SCREW, 8-32X1/2, PFH, ZNC
25	40-25128-1008	SCREW,10-16X5/8, HI-LO ZNC
26	<a href="#">60-12486-0001</a>	ASSEMBLY, SWITCH, RKR,101A/101X, 120
27	60-16138-0002	POWER PACK, 120/127VAC
28	60-16477-0004	CABLE W/RJ45 MALE CONN,3'90END
29	<a href="#">60-22715-0002</a>	CONTROLLER, ENERGY
30	60-19910-0004	DRIVER, FULHAM, 24V
31	60-24826-7XXXX <sup>1</sup>	ASSEMBLY, LED, CENTER, OP7
32	60-24827-7XXXX <sup>1</sup>	ASSEMBLY, LED, END, LEFT
33	60-24828-7XXXX <sup>1</sup>	ASSEMBLY, LED, END, RIGHT
34	60-24885-0003	CLIP, MOUNT, CENTER, OP7 FIXTURE
35	60-24886-0001	CLIP, MOUNT, END, OP7 FIXTURE

\*Items 2 and 3 are not listed as they are not replaceable parts.


<sup>1</sup> Part Numbers are based on length.

## Section 10 – Door Replacement Parts

The following section list Frame Replacement parts for both Normal Temperature and Low-Temperature Door.

**Figure 10.1 Door Assembly for Infinity 90 Series Door, for Replacement Parts**

(See Table 10.1 for part numbers)



**NOTICE**



**Note:** Parts depicted in Red can be replaced, parts in Black are not replaceable.  
\* Exploded assembly for configurations with Vista Arch Handle. For configurations that have a full-length handle, all listed parts are the same apart from the Vista Arch Handle Item #3.

**Table 10.1 Door Assembly for Infinity 90 Series Replacement Parts List**

ITEM NO.	PART NUMBER	DESCRIPTION
1	02-10308-000X <sup>1</sup>	ASSEMBLY, TORQUE ROD
2	02-14649-0000	ASSEMBLY, HOLD OPEN FORK
3	02-17272-0000 <sup>2</sup>	ASSEMBLY HANDLE, ARC, DOOR, VISTA
4	02-25123-2008	ASSEMBLY, GASKET & MAGNET, ACII (S-LIFEPLUS)
5	15-14707-0001	HOLD OPEN FORK, CLOSED END
6	20-15707-0002	CAP, VINYL, HOLD OPEN, RED
7	20-25023-F020 <sup>1</sup>	FAB, COVER, RAIL, DOOR, HEIGHT, HINGE
8	20-25024-F020 <sup>1</sup>	FAB, COVER, RAIL, DOOR, HEIGHT
9	40-11248-0000	SCREW, 8-32X3/16, PHILLIPS TRUSS HEAD
10	40-14616-0001	STANDOFF, PIVOT, HOLD OPEN
11	40-15096-0001	BOLT, DETENT, HOLD OPEN
12	40-15097-0001	SPACER, DETENT, HOLD OPEN
13	60-10848-0002	ASSEMBLY, PLUG, HINGE PIN, DUMMY


<sup>1</sup> Part Numbers are based on length.


<sup>2</sup> Part Numbers are based on finish.

\* Item 3 only applies to configurations with a Vista Arch Handle

## Section 12 – Optimax 7 LED Lighting Fixture Replacement

All work performed must be done by a qualified personal only. All local and national electrical codes must be followed when replacing fixtures of the lighting system. Part numbers referenced in the following instructions can be purchased from the Anthony Parts Department if they are not available at your location.

WARNING	
	<b>Warning</b> – Ensure to cut the power source to the frame to avoid the risk of electrical shock when replacing LED fixtures.

WARNING	
	<b>Warning</b> – To prevent wiring damage or abrasion, do not expose wiring to edges of sheet metal or other sharp objects.

WARNING	
	<b>Warning:</b> For use inside a commercial refrigeration case with packaged foods only.


### Replacement Part Numbers

Hardware for Center Fixtures		
Description	Part Number	Qty Required
Center mounting Clip	60-24885-0003	1
Mounting screw for Center Clip	40-10994-1005	1
Mounting screw for OP7 Center Led Fixture	40-25072-1005	2

Hardware for End Fixtures		
Description	Part Number	Qty Required
End mounting Clip	60-24886-0001	1
Mounting screw for End Clip	40-12514-3010	1
Mounting screw for OP7 End Led Fixture	40-11114-1011	2

## Replacement Instructions

The following instruction set will guide you on how to properly replace an Optimax 7 LED fixture. These instructions can be used for both Center and End Fixtures.


<b>WARNING</b>	
	<p><b>Warning</b> –Make sure to turn off the Light switch on the Frame Mullion (right most) before starting the replacement process.</p>

<b>PROTECTIVE GEAR NOTICE</b>	
	<p><b>Protective Eyewear</b>– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</p>
	<p><b>Protective Gloves</b>– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</p>
	<p><b>Footwear Protective</b> – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</p>


1. Remove the Zipper strips and contact plates on the Frame Mullion to reach the wiring of the existing light.



2. Disconnect the connector on the Led fixture cable from the frame wire Harness connector.



- Using a Philips head screwdriver, remove the mounting screws from the top and bottom of the existing light.



**WARNING**



*Warning: Do NOT use a power drill to remove or install the screws that secure the fixture onto the frame, doing so can damage the frame and strip the threaded hole.*

- Gently remove the LED fixture cable from the wire egress of the mullion/Jamb.
- Remove the Led Fixture by unsnapping the fixture from the Center mounting clip.



- Take the new Replacement OP7 light and feed the Light cable through the wire egress.
- Make a connection between the connector on the Light cable and the Wiring Harness inside the Frame Mullion/Jamb. Make sure the Grommet on the Light cable rests in the egress hole.
- Align the Light fixture mounting bracket holes to the pre-existing mounting holes on the Mullion/Jamb and Snap the OP7 Light fixture into the Center mounting clip.
- Using a Phillips Head screwdriver and the existing mounting screws install the new LED light. Use new screws from the hardware kit if needed.
- Test the lights by turning on the light switch to make sure the connections are secure.
- Place the contact plates back and secure them using the zipper strips. (Use new zipper strips if necessary).
- Repeat the same process for the remaining Mullions and the end Jamb to replace the Lights.

### End Jambs

For end jambs, it may be necessary to remove zipper strips and additionally remove the contact plate of the Frame Sill see images and note below.





#### NOTICE



*Note: For End Jambs, you may need to remove the contact plate of the Frame sill (bottom) to be able to remove the End Jamb contact plate.*

## Section 13 – Removing & Replacing the Torque Rod


Please read the instructions in their entirety. It should answer most of your installation questions. For personal and system safety, and optimum product performance, make sure you thoroughly understand the contents before installing, using, or maintaining this product.

PROTECTIVE GEAR NOTICE	
	<i>Protective Eyewear– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</i>
	<i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i>
	<i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i>

You must remove the door from the frame and place a steady flat surface to remove and replace the torque rod. Once the door is safely on a secure working surface use the following instructions to remove and replace the torque rod.


- Carefully place a flathead screwdriver between the door rail and the washer beneath the torque rod. Refer to Figure 13.1.


**Figure 13.1 Torque Rod location.**



- Dislodge the torque rod from its mount by pushing on the torque rod or tapping it loose using a plastic or rubber mallet. Refer to Figure 13.2.


Figure 13.2 Removing torque rod from the door.




WARNING	
	<p><i>Warning: DO NOT use a steel-headed hammer. Use caution when striking any tool with another tool. DO NOT use excessive force when striking the screwdriver and potentially damaging the door.</i></p>

3. Continue to carefully tap the torque rod, if necessary, until the torque rod and rod end disengages.
4. Carefully pull the torque rod assembly completely out the door rail.
5. Reverse the process to re-install the torque rod assembly into the door rail. Refer to Figure 13.3.
  - Insert torque rod into the bottom of the door until it is fully seated.
  - If required, tap the torque rod assembly into the door rail using a plastic or rubber mallet, until the torque rod is fully seated into the door rail socket.

Figure 13.3 Removing torque rod from the door.






6. Once this is completed, re-install the door per instructions in Section 4 – Door Installation.

WARNING	
	<p><i>Warning: Ensure to apply a minimum of 3 grams of dielectric grease (Anthony P/N: 98-25497-0001) to fill the holes in the socket as shown in Figure 4.2 in “Section 4 – Door Installation”.</i></p>

## Section 14 – Removing & Replacing the Hold-Open Assembly

Please read the instructions in their entirety. It should answer most of your installation questions. For personal and system safety, and optimum product performance, make sure you thoroughly understand the contents before installing, using, or maintaining this product.

You must remove the door from the frame and place a steady flat surface to remove and replace the hold-open assembly. Once the door is safely on a secure working surface use the following instructions to remove and replace the hold-open assembly.


PROTECTIVE GEAR NOTICE	
	<i>Protective Eyewear– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</i>
	<i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i>
	<i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i>

### Removing the Hold-Open Assembly

1. Remove screws from the hold-open standoffs, which are located on the door rail and frame. Refer to Figure 14.1.
2. Remove the hold open, standoffs, and discard them.
3. When replacing the hold-open arm, reverse Step 1 by inserting the screw through the mounting hole in the arm and tightening it into the frame mounting hole using the #2 Philips head screwdriver. Refer to Figure 14.1.

**Figure 14.1** Removing hold-open assembly from door.




NOTICE	
	<i>Note: Parts depicted in Red can be replaced, parts in Black are not replaceable</i>

## Replacing the Hold-Open Assembly




1. Insert the pivot standoff into the [door](#).
2. Add Loctite #271 to threads. Torque to 100 in/lb.
3. Place the pivot hole of the new hold open over the pivot standoff that is closest to the hinge pin.
4. Retain with a new truss head screw and torque to 16 in/lb. (approximately #2 clutch setting on a professional screw gun).
5. Remove the vinyl cap from the detent bolt.
6. Insert the bolt up thru the hold open slot and then thru the detent spacer (flat side against frame).
7. Add Loctite #271 to threads. Use a 7/16 hex wrench and torque into the frame to 100 in/lb.
8. Add a small amount of grease to the detent surface.
9. Ensure the truss head screw is seated on the end of the standoff and not the hold open.

**Figure 14.2 Hold-open Assembly**




## Section 15 – Removing & Replacing the Hinge Pin


The following instructions will guide you on how to remove and replace the Hinge Pin assembly from your **door**.

PROTECTIVE GEAR NOTICE	
	<i>Protective Eyewear– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</i>
	<i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i>
	<i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i>

1. With the access cover removed, pull the hinge pin wires out and separate all three wires (Hot, Neutral, and Ground) from the **door** wire harness by carefully pulling the terminations apart.
2. Using a flat-head screwdriver, pry the hinge pin loose from the mount in the top **door** frame rail.
3. Pull the hinge pin out of the **door** frame until the pin and the wires are completely removed.



4. When replacing the hinge pin, insert all three wires into the hinge pin hole in the **door** rail.




5. Thread the wires through the rail to the access opening.



6. Connect the hinge pin wires to the terminated **door** wires.
7. Insert the remainder of the hinge pin into the frame mounting hole until the hinge pin is fully seated.
8. Harness wires together using a tie-wrap and insert the harness into the **door** rail and install the access cover.
9. Ensure to apply high viscosity dielectric grease to the Hinge Pin receptacle. For doors in Harsh ambient conditions, it is recommended to use a minimum of 3 grams of dielectric grease (Anthony P/N: 98-25497-0001) to fill the holes in the Hinge Pin receptacle socket as shown below.



10. Once dielectric grease is applied correctly, Proceed to re-install the **door** per instructions in "Section 4 -Door Installation".






**WARNING**



**Warning:** Ensure to apply a minimum of 3 grams of dielectric grease (Anthony P/N: 98-25497-0001) to fill the holes in the socket as shown in Figure 4.2 in "Section 4 – Door Installation".


## Section 16 - Torque Master Replacement

The following instructions will guide you on how to remove and replace Torque Master from the frame.


PROTECTIVE GEAR NOTICE	
	<i>Protective Eyewear– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</i>
	<i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i>
	<i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i>

1. Once the first door is removed, proceed to remove, and replace Torque Master.
2. Insert a flat head screwdriver into the Torque Master and turn Counterclockwise to disengage and remove the old Torque Master as shown in Figure 16.1.
3. Next, place the new Torque Master into the opening in the frame, and using a flathead screwdriver turn Clockwise to lock Torque Master in place.

**Figure 16.1: Torque Master Replacement**



4. Ensure that Torque Master is secure before proceeding.
5. Re-install **door** per instructions in Section 4 - **Door** Installation.

<b>WARNING</b>	
	<p><b>Warning:</b> Ensure to apply a minimum of 3 grams of dielectric grease (Anthony P/N: 98-25497-0001) to fill the holes in the socket as shown in Figure 4.2 in "Section 4 – <b>Door</b> Installation".</p>

## Section 17 – Pass-Thru Frame and Door Installation

### Tools Required

The following is a list of all the different equipment, tools, materials, and other things you will need when installing the Anthony 103 Pass-Thru Frame and Doors.

**Equipment:**

- Safe movers
- Dollies
- Ratchet straps
- Clamps
- Narrow pallet jack
- J-bar
- Broom

**Frame Installation:**



- Shims
- Silicone/Butyl
- Caulk gun
- 4' - 6' level
- Rubber/plastic mallet
- Wire stripper/cutter
- Wire nuts
- Tape measure
- Towels / rags

**Tools:**

- Voltage tester
- Soldering Iron
- #2 Philips screwdriver
- Flat-head screwdriver
- Needle-nose pliers
- Razor Knife
- Utility knife
- 5/32" Hex Key
- 7/16 & 1/2" wrenches
- Wireless Drill/Driver

**Materials:**

- Dielectric grease (Anthony P/N: 98-25497-0001)
- NSF Approved Silicone Sealant
- Plywood Shims
- Foam glass cleaner (Ammonia Free)
- Black Paint marker



PROTECTIVE GEAR NOTICE	
	<i>Protective Eyewear– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</i>
	<i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i>
	<i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i>

## Net Opening

Read the instructions in this Section completely before installing the frame. Before installing the frame, confirm that the size of the net opening accommodates the finished frame, the net opening should be larger by 1/8" than the frame size, and there should be a gap of 1/8" on top, and 1/8" on the right side, and 1/8" on the left side. If the gap tolerances exceed 3/8", the net opening will have to be enlarged to reduce the gap within 1/8".

### Pre-Installation Recommendations and Tips

- Proper framing, insulation, and clearances for openings (case bottom or floor are mandated by local building codes).
- Ensure that your opening meets these code requirements before attempting frame installation.
- The sill, Header, and Jack Studs must be completely square, level, and free of any debris that may interfere with the frame sitting flush to the sill.
- If the gap between the frame and the net opening is greater than 1/16", shim the gap for a proper fit (refer to "Shimming Frame").
- Complete replacement of wire assemblies is recommended whenever required. Splice wires only if necessary, using proper materials: such as electrical tape, wire nuts, flux core solder, and heat shrink.
- Apply liquid soap to rail plastic covers and gaskets upon installation to facilitate insertion into mounting grooves.
- Keep doors and frames clean for product efficiency. This can also help reduce energy consumption and potential health hazards.
- Whenever binding **gasket** or plastic parts, use food-grade silicone.
- Always use the correct tool for the job to be performed. This ensures proper installation and minimizes safety risks.
- If there is any doubt about the work to be performed, consult with a certified technician or Anthony representative.
- Preventative maintenance is recommended to ensure product longevity.

<b>PROTECTIVE GEAR NOTICE</b>	
	<i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i>
	<i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i>

## Frame Installation

The following instructions will ensure proper frame installation:

1. When installing the frame, **DO NOT** install the Frame directly on Sheetrock, the frame is designed to be installed on Cooler/Freezer Boxes only
2. Ensure that the Sealing Frame Flap is fully engaged to the Sill, Header, and Jack Studs creating a seal without any gaps (see Figure 17.1)
3. Make sure to **DO NOT** force the frame if the fit is too tight, doing so may cause you to break the Sealing Frame Flap or tweak the Frame.
4. Insert a mounting screw into a mounting hole in each corner of the frame and tighten each screw until it is approximately a quarter inch from being flush.
5. Check the frame is aligned properly or square.
6. Use a measuring tape to measure diagonally from one corner to the opposite and note the distance.
7. Measure the distance between the remaining two corners.
8. Both measurements should be the same, or within a 1/16" difference.
9. Confirm the frame and frame flanges are vertically and horizontally aligned (plumb) to the wall surface around the net opening.
10. Place a level on the top flange of the header frame to check if it is horizontally aligned.
11. If the top of the header frame sags or bows, correct it as necessary.
12. When the frame is completely aligned, tighten all mounting screws securely until each is flush with the frame surface. **DO NOT** over-tighten the screws, as this can cause the frame to become out of square.
13. Check the entire frame to ensure installation is correct. If needed see refer to the "Shimming Frame" section for instructions on how to use shims to align the frame properly.




<b>WARNING</b>	
	<p><b>Warning:</b> <i>DO NOT over tighten screws onto the frame, as this may cause bowing, sagging, or the frame to become out of square. This will cause installation issues with Door's proper function. Adjusted the frame as needed to ensure it is square and free of bowing and sags.</i></p>




Figure 17.1: Frame Alignment, Squareness, and Plumb



<b>WARNING</b>	
	<p><b>Warning:</b> Use only food-grade silicone sealant (add caulking for larger gaps) to seal the gap between the frame and the surrounding wall, inside the case, cooler or freezer. Not following these procedures can void Anthony's Service &amp; Warranty on condensation and ice build-up issues.</p>

## Shimming the Frame


Shimming is only to be used when necessary and will primarily be done at the header (top) of the frame and opening. If the gap between the frame and net opening is greater than 1/16", proceed to shim the gap for a proper fit. If everything is aligned, squared, plumb and gaps do not exceed 1/16" skip the shimming process and proceed to seal the Frame refer to "Sealing the Frame" below for instructions.

PROTECTIVE GEAR NOTICE	
	<i>Protective Eyewear– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</i>
	<i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i>
	<i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i>

The following instructions will ensure to properly shim frame when necessary:




1. Acquire sturdy, penetrable material, such as plywood. The thickness of the material should be wedge-shaped and slightly less than the gap to be filled, remember if the gap is larger than 1/8" opening must be reduced properly to accommodate the frame.
2. When using shims, they must be installed from left to right or top to bottom, **PARALLEL** to frame width or height.
3. Measure the length of the gap (height or width of the frame) and cut the shim material to 1/16 of an inch less than the measured length.
4. Install the shim using the same type of mounting hardware that will be used to install the frame. Be certain that the shim installation hardware will not interfere with the frame installation hardware.
5. If necessary, cut a second shim to the same length and install it on the opposite side of the net opening.
6. If the adjacent sides of the net opening need to be shimmed, repeat the previous steps, matching the shim length to the frame sides of the net opening (less 1/16 of an inch).
7. Shims must **NOT** be used perpendicularly.
8. Excess shim material **MUST** be removed to ensure proper sealing to the frame.
  - A. When the Frame extends past Sill, Header, or Jack Studs ensure that excess shim material does not extend (in-depth, i.e., front to back) past the Sill, Header, or Jack Studs (see Figure 17.2, Example 1 below)
  - B. When Sill, Header, or Jack Studs extend past the Frame ensure that excess shim material does not extend (in-depth, i.e., front to back) past the Frame (see Figure 17.2, Example 2 below)
9. If the adjacent sides of the net opening need shimming, repeat the previous steps. Match the shim length to the frame sides of the net opening (less 1/16").

Figure 17.2: Frame Shimming and Sealing Details



## Sealing the Frame


The electrical connection at the Junction Box where the wires enter the frame, and where the wires enter the raceway in the frame must be sealed with NSF Approved Food Grade Silicone Sealant (RTV-108) at the time of installation. Ensure to seal the gap between the frame and the surrounding wall, inside the case, cooler or freezer. Not following these procedures can void Anthony and Anthony’s Service & Warranty on condensation and ice build-up issues. Refer to Figure 2.2, on the previous page for clarification.


PROTECTIVE GEAR NOTICE	
	<i>Protective Eyewear– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</i>
	<i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i>
	<i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i>

The following instructions will ensure a proper seal of the Frame:

1. Always ensure that you can locate the Foam insert which lines the entire flange around the Frame; DO NOT remove this foam, it is critical to ensure proper insulation.
2. Ensure that the Sealing Frame Flap is fully engaged to, Sill, Header, and Jack Studs creating a seal without any gaps.
3. Ensure that any excess shimming material is removed as instructed above in “Shimming Frame”.
4. If your installation is like Example 1 in Figure 17.2, proceed to seal with Silicone Sealant (RTV-108) as shown.
5. If your installation is like Example 2 in Figure 17.2, proceed to seal with Silicone Sealant (RTV-108) as shown.
6. Ensure to seal the Threshold Plate as shown in Figure 17.3.
7. Follow the manufacturer’s curing instructions for the Silicone Sealant (RTV-108) to ensure proper use.
8. Once Silicone Sealant is cured double-check for any remaining gaps that require more sealant.


**Figure 17.3: Sealing Threshold**




WARNING	
	<b>Warning:</b> Ensure to use silicone approved for use in commercial refrigeration applications which meets all requirements and guidelines. Use only food-grade silicone sealant (add caulking for larger gaps) to seal the gap between the frame and the surrounding wall, inside the case, cooler or freezer. Not following these procedures can void Anthony’s Service & Warranty on condensation and ice build-up issues.


**To Install a Pass-Thru Frame with Threshold**

1. Insert the finished frame assembly into the net opening. **DO NOT** force the frame if the fit is too tight.
2. Insert a mounting screw into a mounting hole in each corner of the frame and tighten each screw until it is approximately a quarter inch from flush.
3. Check the frame is aligned properly or square. Refer to Figure 17.1 Frame Installation Reference.
4. When the threshold is desired, drill and lag on pre-drilled mounting holes only.

NOTICE	
	<i>Note: Use caulk and food grade silicone sealant to seal the gap between the frame and the surrounding wall, inside the case, cooler or freezer.</i>

NOTICE	
	<i>Note: If a Roll-A-Way cart is included in the order, it must be behind the <b>door</b> before installing the frame.</i>


**Figure 17.4: Mounting Holes**



**For Cut Threshold**


Verify the cut threshold is square and plumb to the rest of the frame before drilling through pre-drilled mounting holes. Refer to Figure 17.5 Without Threshold.


**Figure 17.5: Frame Without Threshold**




## Frame Electrical Wiring Connections

The electrical connection at the Junction Box where the wires enter the frame, and where the wires enter the raceway in the frame must be sealed with silicone caulking at the time of installation.

WARNING	
	<p><b>Stop:</b> Wiring for lights should have a separate circuit from the frame heater wiring circuit.</p>

WARNING	
	<p><b>Warning</b> – To reduce the risk of fire, electrical shock or injury observe the following:</p> <ul style="list-style-type: none"> <li>- Use this unit in the manner intended by the manufacturer.</li> <li>- Turn the power off before removing the existing lighting system and follow appropriate lockout/tag-out safety procedures</li> </ul>

WARNING	
	<p><b>Risk of Electrical Shock</b>– Potential risk of Electrical Shock; pay close attention to instructions when performing this and any other associated tasks.</p>


### Conduit Exit Location

For Pass-Thru frames, the conduit exit for connection wires is typically located on the top right inside of the frame. Depending on your needs when ordering you can designate where you would prefer the conduit exit to be located.

**Figure 17.6: Conduit Exit location**



**Figure 17.7: Wiring Labels**






The seven individual wires extending from the flexible conduit atop the frame, provide electrical power to various frame and door functions for the wiring diagram label, affixed to the frame header.

Using wire connectors, these wires should be grouped by the Hotwires (Circuit wires), the Neutral wires, and the ground wire for connection to either the facility or the case power.

- Blue/White wire connects to the supplied Hot (or Lights Circuit Wire).
- White/Blue wire connects to the supplied Light neutral wire.
- Red and Black wires connect to the supplied Hot (or Door/Frame Heater Circuit Wire).
- White/Red and White/Black wires connect to the supplied neutral wire for the Door/Frame Circuit.
- Green/Yellow wire connects to the supplied ground wire.




Figure 17.8: Wiring Diagram



NOTICE	
	<p><i>Note – Wiring for lights should have a separate circuit from the <b>door/frame</b> heater wiring circuit.</i></p>


## Section 18 – Pass-Thru Door Installation

Following the instructions will guide you on how to Install the Pass-Thru Door Assembly on Pass-Thru Frame.

PROTECTIVE GEAR NOTICE	
	<i>Protective Eyewear– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</i>
	<i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i>
	<i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i>

1. Hold the door on each side, with the handle facing forward. Lift door, align torque rod to insert into TorqueMaster™ socket at the base of the frame.

**Figure 18.1: Inserting door Torque Rod into TorqueMaster**



2. Now we will proceed to engage and lock the hinge pin into place, and prepare the SOCKET (hinge pin plug) receptacle by using Dielectric grease on the socket of the frame before inserting the door hinge pin. (Anthony P/N: 98-25497-0001).
3. Apply a minimum of 3 grams of dielectric grease (Anthony P/N: 98-25497-0001) to fill the holes in the socket as shown in Figure 18.2.

**Figure 18.2: Dielectric Grease in SOCKET (hinge pin plug) receptacle**



4. Engage **door** with hinge pin inserted into SOCKET (hinge pin plug) receptacle at top of the frame. Push the **door** into the frame until the hinge pin snaps in place. See Figure 18.3.

**Figure 18.3: Connect Hinge Pin**



5. Insert the hold-open bolt through the elongated hold-open slot.
6. Insert the hold open through stand-off and secure it with a Phillips screw (provided) using a #2 Philips screwdriver. Keep the screwdriver perpendicular to the screw head. Make sure the tip is fully seated into the screw head recess before turning.
7. Set the **door** tension swing and correct the **door** alignment by adjusting the TorqueMaster™. (See TorqueMaster™ and Sag Adjustment).

Figure 18.4: Tighten Hold-Open Screw



**NOTICE**




*Note – DO NOT use power tools to install the hold-open screw. Exercise caution when handling the **door**. DO NOT over-tighten the hold-open bolt. Verify hold-open does not bind while sliding along the hold-open bolt. Adjust as necessary.*


**To Remove the Door Assembly**

1. Release tension on TorqueMaster™ with a flat-head screwdriver. Turn the TorqueMaster™ front facing screw clockwise, until the door does not automatically close from an open position.

**Figure 18.5: Release TorqueMaster Tension**



2. Open door to access the hold open device, then loosen and remove the hold open using a Phillips #2 screwdriver.

NOTICE	
	<i>Note –<u>DO NOT</u> use power tools when adjusting the TorqueMaster™.</i>

**Figure 18.6: Remove Hold-Open**



3. Retract the door to a near-closed position.

4. Remove the hinge pin plug from the frame by inserting the top half of needle-nose pliers into the spring clip grip hole and the bottom half beneath the hinge pin shroud.

**Figure 18.7: Disengage Hinge Pin**




5. Compress pliers to clamp down on the hinge pin spring clip, then simultaneously pull the hinge pin away from the frame and pull the door top out.

**Figure 18.8: Withdraw Away from Hinge Gib**



6. Lift door out of TorqueMaster™. Secure or lean the door on its side against a stable surface.

**Figure 18.9: Withdraw from Frame**




### Hold Open

Once all hinges are installed, use the following instructions to install the hold open.

1. Position the hold open onto the pivot and screw on tightly.
2. Once the hold open is in place, ensure everything closes and opens with ease. If not, ensure all hinges are correctly placed and screws are fully tight.
3. If the door does not close with ease, adjust the height of the bottom wiper by loosening the screws and adjusting the height. When the door is properly in place, torque must be added to the hinges.

**Figure 18.10: Hold Open**




4. With the wrench key in hand, rotate the adjustment capstan clockwise. Rotate the pin approximately 1.5 turns, until the fourth hole is reached.

## Section 19 – Pass-Thru Frame Replacement Parts

The following section list Pass-Thru Frame Replacement parts.

**Figure 19.1 Frame Assembly for Infinity 90 Series NT Pass-Thru; Replacement Parts**

(See Table 19.1 for part numbers)



### NOTICE



**Note:** Parts depicted in Red can be replaced, parts in Black are not replaceable.  
The exploded view illustrates a configuration with a bottom floor threshold some configurations may not come with a threshold

**Table 19.1 Frame Assembly for Infinity 90 Series NT Pass-Thru Door Replacement Parts List**

ITEM NO.	PART NUMBER	DESCRIPTION
1	02-10568-000X <sup>2</sup>	ASSEMBLY, TORQUE MASTER, #1, BLACK
2	02-24652-0000	ASSEMBLY, ENCLOSURE, DRIVER, REMOTE
3	02-25060-0001	ASSEMBLY, FRAME, CONDUIT FLEX , 90° EXIT
4	15-12520-F091 <sup>1</sup>	FAB, PLATE, CONTACT, LH, 103N
5	15-12520-F092 <sup>1</sup>	FAB, PLATE, CONTACT, RH, 103N
6	15-12520-F093 <sup>1</sup>	FAB, PLATE, CONTACT, HEADER, 103N
7	20-24915-1023	EXT, RETAINER, FR & MUL, 101N, BLACK
8	40-11114-1011	STANDOFF, PIVOT, HOLD OPEN
9	60-24827-0000	ASSEMBLY, LED, END, LEFT
10	60-24828-0000	ASSEMBLY, LED, END, RIGHT

<sup>1</sup> Part Numbers are based on length.


<sup>2</sup> Part Numbers are based on finish.

## Section 20 – Pass-Thru Door Replacement Parts

The following section list Pass-Thru Frame Replacement parts.

**Figure 20.1 Door Assembly for Infinity 90 Series NT Pass-Thru; Replacement Parts**

(See Table 20.1 for part numbers)



**NOTICE**



*Note: Parts depicted in Red can be replaced, parts in Black are not replaceable; Optional Kickplate not shown in drawing above.*

**Table 20.1 Door Assembly for Infinity 90 Series NT Pass-Thru Door Replacement Parts List**


ITEM NO.	PART NUMBER	DESCRIPTION
1	02-10308-0002	ASSEMBLY, TORQ ROD
2	02-14649-0000	ASSEMBLY, HOLD OPEN FORK. 101N
3*	02-18746-0001	ASSEMBLY, GASKET & MAGNET, PASS-THRU, 403N
	02-24232-0000	ASSEMBLY, GASKET & MAGNET, AIRCELL II, PASS-THRU
	02-24812-0000	ASSEMBLY, GASKET & MAGNET, AIRCELL II, 2 SIDED PVC
4	40-11117-1011	SCREW, 8X1, AUTOBODY OVL
5	04-16773-0000 <sup>2</sup>	OPTION, PUSH BAR
6	04-16882-0000 <sup>2</sup>	OPTION, BAR, BUM, I/S, 101B/401B
7	15-14707-0001	HOLD OPEN, FORK CLOSED END
8	20-11435-F000	FAB, SEAL, P-THRU DR, FL, WIPE
9	20-15707-0002	CAP, VINYL, HOLD OPEN
10	20-24955-XXXX <sup>1</sup>	FAB, COVER, RAIL, DOOR, 101N
11	40-10946-7008	SCREW, 10-24X5/8 SHC W/NYLON
12	40-11248-0000	SCREW, 8-32, TRUSS HD, HOLD OPEN SCREW
13	40-12013-0001	ASSEMBLY, LOCK, CYLINDER
14	40-14616-0000	STANDOFF, PIVOT, HOLD OPEN
15	40-15096-0001	BOLT, DETENT HOLD OPEN
16	40-15097-0001	SPACER, DETENT, HOLD OPEN
17	45-17239-000X <sup>2</sup>	HANDLE, ASSEMBLY, VISTA ARCH
18	60-10848-0002	ASSEMBLY, PLUG, HINGE PIN, DUMMY

<sup>1</sup> Part Numbers are based on length.

<sup>2</sup> Part Numbers are based on Finish.

\*For ITEM 3: The replacement gasket for your Pass-door is dependent on which configuration of door you have. Refer to figure 20.2.

**Figure 20.2 Door Assembly for Infinity 90 Series NT Pass-Thru; Replacement Parts**



---

## Appendix A - **Gasket** Replacement Guidelines

Please read the guidelines in their entirety. It should answer most of your installation questions. For personal and system safety, and optimum product performance, make sure you thoroughly understand the contents before installing, using, or maintaining this product.

### Preliminary Considerations for Servicing Gaskets

#### Tools Required

Rubber or plastic mallet  
Heat gun




#### Recommendations and Suggestions

- When needed, apply liquid soap to rail plastic covers and gaskets upon installation, to facilitate insertion into mounting grooves.
- Keep doors and frame surfaces clean for product efficiency. This can also help reduce energy consumption and potential health hazards.
- Whenever binding **gasket** or plastic parts; use food-grade silicone.
- Always use the correct tool for the job to be performed. This ensures proper installation and minimizes safety risks.
- If there is any doubt about the work to be performed, consult with a certified technician or Anthony's representative.
- Preventative maintenance is recommended to ensure product longevity.

### Ordering Replacement Gaskets

Ordering your authentic Anthony replacement gaskets for your doors is easy, visit us at [www.anthonystore.com/en](http://www.anthonystore.com/en) to place orders, look up past work orders, and get quotes fast and easy.

## Gasket Removal

PROTECTIVE GEAR NOTICE	
	<i>Protective Eyewear– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</i>
	<i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i>
	<i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i>

To remove the **gasket** from the **door**, follow the steps below:


1. To remove, carefully pull the **gasket** straight out of the groove between the **door** rail and plastic cover starting at the top corner of the **door**.






2. Carefully pull the **gasket** out and downward of the groove in the plastic rail covers.



- Continue to pull the **gasket** from the Plastic rails gently around the entire perimeter.

WARNING	
	<p><i>Warning – Warning: The <b>gasket</b> is composed of soft materials with welded miter joints. Use extra care when manually extracting the <b>gasket</b> from the rail grooves to prevent damaging it as well as the plastic rail.</i></p>

## Gasket Installation

PROTECTIVE GEAR NOTICE	
	<p><i>Protective Eyewear– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</i></p>
	<p><i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i></p>
	<p><i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i></p>

To install the **gasket** onto the **door**, follow the steps below:

- Carefully align the two corners of the replacement **gasket** onto the top corners of the plastic cover, with the **gasket** arrow facing the **door** rail and cover.



- With the corners aligned, press the arrows of the **gasket** into the **gasket** retainer groove and press firmly on the **gasket** until the **gasket** is seated into the groove and corners.



3. Continue to insert the **gasket** arrow into the groove around the perimeter of the **door** surface by pressing the **gasket** firmly against the plastic cover, sliding from side to side, and applying full pressure against the **gasket**, forcing the **gasket** arrow into the groove in the plastic.


- When you get near the bottom of the **door**, carefully align the two bottom corners of the **gasket** onto the bottom corners of the plastic cover, with the **gasket** arrow facing the **door** rail and cover.




- Continue to insert the **gasket** arrow into the groove around the remaining perimeter of the **door** surface by pressing the **gasket** firmly against the plastic cover, sliding from side to side, and applying full pressure against the **gasket**, forcing the **gasket** arrow into the groove in the plastic.





- Confirm that the entire **gasket** arrow has been completely inserted into the groove of all four plastic rail covers.

WARNING	
	<p><i>Note: Pay careful attention that the arrows are firmly pressed into the grooves at the corners. A rubber mallet can be utilized if the arrows do not easily insert into the grooves.</i></p>

WARNING	
	<p><i>Note: If the <b>gasket</b> has any signs of deformation from the packaging it is acceptable to use a low heat blower to warm the <b>gasket</b>. This can be performed by blowing warm air on the gaskets in a sweeping motion to warm the gaskets between 80°F and 110°F so the <b>gasket</b> can reshape.</i></p>

## Appendix B – Door Reversal

Please read the guidelines in their entirety. It should answer most of your installation questions. For personal and system safety, and optimum product performance, make sure you thoroughly understand the contents before installing, using, or maintaining this product. Some doors are reversible.

PROTECTIVE GEAR NOTICE	
	<i>Protective Eyewear– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</i>
	<i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i>
	<i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i>

Remove the **door** from the frame first and then perform the following steps:

### Frame

1. To remove TorqueMaster, insert a flat-head screwdriver into the top center cutout in TorqueMaster, and turn the mounting screw counter-clockwise for less than ½ turn. Lift TorqueMaster off the frame.



2. Pry off (underneath) the plug cap from the mounting hole, on the opposite side of the doorframe with a flat-head screwdriver.



3. Set TorqueMaster onto the opened mounting hole. Align the flanged corners of the mounting tabs with the SAG ADJUSTMENT screw facing the inside of the frame.
4. Use the flat-head screwdriver and turn the TorqueMaster mounting setscrew clockwise for ½ turn, to tighten the mounting flange and lock it in place.



5. Relocate and install the hold-open stand-offs and spacer into the opposite hold-open mount of the same door opening on the frame.



## Door

1. Access the hinge pin wire connections in the rail on the hinge side of the **door** assembly. Disconnect the Hot, Neutral, and Ground wires of the hinge pin.



2. Loosen and remove the hinge pin assembly from the top **door** rail.
3. Using a plastic mallet and a flat-head screwdriver, remove the torque rod from the bottom of the **door** assembly.



4. Reinstall the hinge pin and the torque rod on the opposite ends of the **door** assembly.
5. Reconnect the hinge pin wires and confirm all connections.
6. See "Section 4 – **Door** Installation" on how to re-install and for TorqueMaster and Sag adjustment instructions.

### WARNING




*Warning: Ensure to apply a minimum of 3 grams of dielectric grease (Anthony P/N: 98-25497-0001) to fill the holes in the socket as shown in Figure 4.2 in "Section 4 – **Door** Installation".*

## Appendix C – Anti-Fog Maintenance

The PET Film on your Anthony product is a scratch-resistant, permanent coating that prevents fogging and icing of cold surfaces. On transparent substrates, it provides a clear view (i.e., through a refrigerator **door** when opened). Described herein are the cleaning instructions should only be performed only by personnel that is qualified and/or fully understand the specific tasks in accordance with this documentation, in particular its warning notices, safety instructions, and the non-use of harmful chemicals which will hinder the effectiveness or damage the PET Film.

The PET Film coating absorbs moisture on its surface as well as absorbs water vapor within its volume. Therefore, it does not only spread water drops to improve visibility at temperatures above 0°C but also inhibits the formation of ice crystals on the surface. In a refrigerator, after closing the **door**, this function is regenerated by the absorption of water into the dry inner atmosphere. Although it absorbs moisture, the coating does not dissolve in water, so it will not smudge when wet.

<b>WARNING</b>	
	<p><b>Warning:</b> Any cleaners which contain abrasives may not be used. Do not contaminate the <b>door</b> with silicone. Do not use tape, glue, stickers, attachments, magic markers, or similar products on the film coating. Do not use razor blades or other mechanical devices to remove foreign residue or objects directly on film coating. Do not use abrasive cleaners or materials on the film coating like Ajax®, Scotch Brite®, or Steel Wool. Do not use cleaners or materials that contain silicone oils or waxes, these hinder the anti-fog performance by leaving residue and/or damage the film coating surface. Examples of these types of cleaners include and are not limited to ArmorAll®, Tilex®, Bleach, Windex® No-Drip, Windex® Wipes, Pledge®, or any product containing silicone oils or waxes.</p>

### Care and Cleaning

Initial wetting/washing with water is recommended to reach full function.

Cleaning can be performed using common household glass cleaners (Sidolin®, Windex®, Mr. Muscle®) and a tissue or paper towel. However, on very cold surfaces these cleaners may freeze. In these cases, a mixture of 30% pure alcohol and water may be used. At temperatures above 0°C, warm hand temperature water with a mild detergent can be applied.

Other recommended cleaners include:

- Greased Lightning®
- Mr. Clean (degreasing cleaners)
- Windex® Vinegar
- Mean Green®
- Formula 409® Grease & Grime
- Fantastik®
- Windex® original
- MicroClean Professional APC® (formerly Now® all-purpose cleaner)

Recommended cleaning is with a soft dry or slightly damp towel, or with one of the degreasing cleaners listed above. If you have any questions about the use of a particular cleaner, please contact Anthony (800) 772-0900.




<b>WARNING</b>	
	<p><b>Warning:</b> Failing to abide by the following cleaning instructions will result in a loss of Anthony Factory Warranty.</p>

Ajax® is a registered trademark of Colgate-Palmolive Company. | ArmorAll® is a registered trademark of Armored Auto Group. | Fantastik®, Pledge®, Mr. Muscle®, and Windex® are registered trademarks of S.C. Johnson & Son, Inc. | Formula 409® and Tilex® are registered trademarks of The Clorox Company. | Greased Lightning® is a registered trademark of HomeCare Labs. | Mean Green® is a registered trademark of CR Brands, Inc. | MicroClean Professional APC® (formerly Now® all-purpose cleaner) is a registered trademark of The Mirachem Corporation. Mr. Clean Top Job® is a registered trademark of Procter & Gamble. | Scotch Brite® is a registered trademark of 3M. | Sidolin® is a registered trademark of Thompson-Siegel Gessellschaft Mit Beschraenkter Haftung GmbH.

## Appendix D – POM Lock Installation


The POM lock is the only lock currently available for your doors. The POM Lock offers a quick and easy locking mechanism to help keep your doors locked when needed.

There are two (2) different part numbers for the POM lock when ordered. Which Part you will need is determined by the type of frame that is present. If the frame has GIBS (see Figure D.1 and D.2), use Part Number: [02-11585-0003](#); this will include POM Lock and Key only.

PROTECTIVE GEAR NOTICE	
	<i>Protective Eyewear– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</i>
	<i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i>
	<i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i>

Use Part Number: [02-14288-0001](#) if a Retro-fit kit is needed. This usually is the case for models WITHOUT Gibs in the frame and frames with locks mounted on the bottom of the [door](#).

**Figure D.1: Pom Lock Specifications**




## Standard POM Lock

Follow the instructions below to install the POM lock onto your cooler Doors.


1. Remove the dummy plug from the hinge pin access plate on top of the frame on the handle side of the door.

**Figure D.2: Plug Removal**



13. The POM Lock inserts into the hinge pin access plate.


**Figure D.3: Hinge Pin Access Plate (lock retainer)**



14. Insert the key into the POM Lock square keyhole, then turn the key counterclockwise to lock.
15. Remove the key.
16. To remove the POM Lock, insert the key into the square keyhole and turn the key clockwise.

17. To remove the lock, pull the lock straight out.
18. Replace the dummy plug.
19. Only lock the side that inserts into the hinge pin access plate.
20. Facing the POM Lock; the lock on the right side is for left-hinged doors, and the lock on the left side is for right-hinged doors.


**Figure D.4: Front View POM Lock**



21. The POM Lock is always installed in the frame, over the top of the handle rail side of the [door](#).
22. To retrofit the POM Lock on existing doors in the field, contact Anthony Customer Service or the local Sales Representative in your area for information and instruction sheets. Or follow instructions provided in "Appendix E – Retrofitting for POM locks".

## Appendix E – POM Lock Retrofitting

The POM lock is the only lock currently available for all Anthony Door Models. The POM Lock offers a quick and easy locking mechanism to help keep your doors locked when needed. The following instructions will guide you on how to retrofit an existing installation.

PROTECTIVE GEAR NOTICE	
	<i>Protective Eyewear– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</i>
	<i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i>
	<i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i>


**Figure E.1: POM Lock Retrofit Kit**



The following are instructions on how to Retrofit your doors/frame for the installation of POM Lock:


1. To install the retrofit retainer, measure over 1-1/2" from the edge of the door (handle side) and mark the frame above the door.

**Figure E.2: Template Offset location**




2. Place the template provided on the frame with the right edge of the template on the mark created in Step 1.

**Figure E.3: Template Placement on Frame Side view**




3. Mark the frame through the five holes on the template with a pencil. Remove the template and center punch the marks on the frame.
4. Drill the four outboard holes with an 11/64" drill, and the center hole with a 5/8" drill. Deburr the holes.
5. Place the retrofit retainer bracket over the holes with a rectangular notch cut out. Use #10-32 x 5/16" screws provided and mount the retainer bracket to the frame.
6. Insert the POM Lock into the access plate and turn the key counterclockwise to lock.

**Figure E.3: Access Plate Assembly**






7. Remove the key.
8. To remove the POM Lock, insert the key into the square lock hole and turn the key clockwise.

**Figure E.4: Front View POM Lock**



## Appendix G – Cylinder Lock Replacement

The following section is only for Anthony Door Models with cylinder locks installed. The cylinder lock offers a quick and easy locking mechanism to help keep your Doors locked when needed. The following instructions will guide you on how to replace an existing cylinder lock.

PROTECTIVE GEAR NOTICE	
	<i>Protective Eyewear– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</i>
	<i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i>
	<i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i>

**Figure G.1: Cylinder lock strike location**





Figure G.2: Cylinder lock exploded view



1. Remove **gasket** from **door** rail containing the lock (leaving the **gasket** on the remaining **door** rail assembly for easy reassembly).
2. Remove plastic cover from the **door** rail containing the lock assembly to expose access to the lock mount.
3. Insert a large Phillips-head screwdriver into the lock access at the back of the **door** rail. See Figure G.3A.




NOTICE	
	<p><i>Note: Once the lock screw has been removed, the screw washers and lock latch will come loose. Be certain that these components are secure before the removal of the lock screw, or they may become lost if dropped inside of the <b>door</b> rail. Refer to Figure G.3B.</i></p>

Figure G.3: Lock Screw removal




4. Turn the lock screw counterclockwise to loosen the screw.
5. Carefully remove the screw, lock washers, and lock strike from the back of the lock assembly. Refer to Figure G.3B.
6. If necessary, replace the strike. Refer to Figure G.4.
7. Remove the lock assembly, out from the lock housing and through the front of the door rail. Refer to Figure G.4.
8. Replace lock assembly into housing inside rail.
9. Replace the strike washer, strike, lock washer, and screw to the rear of the lock assembly and assemble in the correct order. Be certain that the strike is fully and correctly seated onto the end of the cylinder.
10. Turn the lock screw clockwise to catch the threads and tighten the screw completely.

<b>WARNING</b>	
	<i>Warning: NOT OVER-TIGHTEN. Refer to Figure G.6.</i>


**Figure G.4: Lock cylinder assembly removal**




**Figure G.5: Strike Plate replacement**



**Figure G.6: Cylinder lock assembly replacement**






**Figure G.7: Secure Lock**



11. Test lock and confirm that it works properly.
12. Replace the plastic cover and [gasket](#).
13. Re-install [door](#) per instructions in Section 4 – [Door](#) Installation.

# Appendix I – Pass-Thru Door Bottom Wiper Adjustment & Replacement


The following section pertains only to Pass-Thru Doors with bottom wiper seal. The Bottom Wiper can be adjusted and/or replaced as needed. The following instructions will guide you on how to adjust or replace an existing bottom wiper.

PROTECTIVE GEAR NOTICE	
	<i>Protective Eyewear– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</i>
	<i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i>
	<i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i>

### Bottom Wiper Adjustment:

1. To adjust the bottom wiper blade on your Pass-Thru use a #2 Phillips head screwdriver to slightly loosen screws and then slide the entire wiper up or down as needed, ensure that the wiper blade creates a good seal between floor and door eliminating unwanted airflow, as shown in Figure I.1.
2. Once you have adjusted it into place, proceed to tighten all the screws to secure the wiper in place, as shown in Figure I.1.

Figure I.1 – Wiper Adjustment




**Bottom Wiper Replacement:**

1. To replace the bottom wiper blade on your Pass-Thru use a #2 Phillips head screwdriver to slightly loosen all screws and then remove the old bottom wiper, as shown in Figure I.1.
2. Position and align the new bottom wiper with all holes, insert all screws, and tighten enough to and adjust as needed once you have adjusted into place, proceed to tighten all the screws to secure the wiper in place, ensure that the wiper blade creates a good seal between floor and [door](#) eliminating unwanted airflow, as shown in Figure I.1.




## Appendix J – Removing & Replacing Door Rail Plastic Cover

The following section guides you on how to replace a damaged door rail plastic cover located on the back side of your door, behind the gasket, and attached to the door rail. These instructions apply to walk-in models 101N, 101T, and 101B. They also apply to Pass-Thru models 103N, 103T, and 103B. When replacing the Door rail plastic ensure that once complete to proceed to re-install door gasket and/or wipers.

<b>WARNING</b>	
	<p><i>Warning: It is not recommended to replace the Door rail Plastic covers unless necessary.</i></p>

### Tools Required


- Rubber or plastic mallet
- Slot-headed Screwdriver

<b>PROTECTIVE GEAR NOTICE</b>	
	<p><i>Protective Eyewear– Potential risk of eye injuries, protective eyewear required when performing this, and any other associated tasks.</i></p>
	<p><i>Protective Gloves– Potential risk of injury to your hands, protective gloves required when performing this, and any other associated tasks.</i></p>
	<p><i>Footwear Protective – Potential risk of injury to your feet, wearing protective footwear is required when performing this and any other associated tasks.</i></p>

### Removing Plastic Cover

1. Insert the end of a slot-head screwdriver in between two plastic cover ends at the corner miter, as shown in Figure J.1.

**Figure J.1 – Plastic Cover corner miter**




- Carefully twist the screwdriver to loosen the corner of the plastic cover lip from the **door** rail.
- Continue to pry the plastic cover from the **door** rail until the entire end of the plastic rail is disengaged, as shown in Figure J.2.

**Figure J.2 – Prying Plastic Cover**



- Pull the plastic cover up and out of the **door** rail grooves until the entire plastic cover is removed from the **door** rail, as shown in Figure J.3.

**Figure J.3 – Separating Plastic Cover from the door rail**



- Repeat Step 2 through Step 4 to loosen and remove the three remaining plastic covers.

**WARNING**



*Warning: Ensure that when replacing plastic **door** rail covers you remove all leftover adhesive on the **door** rail before installing the replacement plastic **door** rail cover.*


### Installing New Plastic Cover

1. To install the new replacement plastic covers, begin by aligning the replacement plastic cover evenly onto the **door** rail, as shown in Figure J.4.
2. Insert the outer edge of the plastic cover into the outside groove of one of the **door** rails, as shown in Figure J.4.

**Figure J.4 – Installing replacement Plastic Cover**



3. Push the plastic cover down and inward, toward the center of the **door**.
4. Slide along the entire length of the plastic cover while firmly applying pressure against it. Continue applying pressure down along the length of the entire **door** rail, inserting both the outside lip and the inside lip into the **door** rail grooves simultaneously, as shown in Figure J.5.

NOTICE	
	<p><i>Note: Carefully tap the plastic cover using a plastic or rubber mallet with deliberate strokes, outward and away from the glass, which may help seat the lips of the plastic cover into the grooves of the <b>door</b> rails.</i></p>

**Figure J.5 – Applying pressure**



5. Check the entire plastic cover and confirm that both the inside and outside lips are fully inserted into the **door** rail grooves.
6. Repeat this procedure, aligning each mitered corner, with the remaining plastic covers until all four plastic covers are properly installed onto **door** rails.
7. Confirm that each plastic cover is fully installed, and the mitered corners properly aligned.

Once you complete installing/replacing **door** rail plastic proceed to re-install gaskets as instructed in “Appendix A – **Gasket Replacement Guidelines**” and re-install the **door** according to instructions that can be found in this manual.

## Appendix K – Anthony Energy Controller

The main purpose of the Anthony's Energy Controller to maintain the Frames and Doors from condensation. The Energy Controller manages the Anti-sweat heat on the Frame based on the Frame temperature sensor reading. Anti-condensate heat is activated when the Frame temperature sensor temperature reads equal to or less than (Dew point Temperature + 10°F). At 75°F Ambient Temperature and 55% Relative Humidity, the Dew point temperature is 58°F, so the Cut off temperature for the sensor is 68°F. The Energy Controller comes standard factory installed on all Domestic (US & CANADA) Anthony Walk-In Cooler/Freezer Frames and is ideal for both cooler and freezer applications in high and low humidity environments.


### Features

- The Anthony Energy controller activates the Frame heat when the Frame temperature sensor reads equal to or less than (Dew point Temperature + 10°F).
- The LED sensor is turned on constantly and appears in "RED" when the Heat is On. It turns off when the heat is Off.

### Location

- The Energy controller is typically located in the Mullion that houses the LED Driver.
- The humidity sensor (Dew point sensor) is located on the Frame Header on the right side of the Frame.
- The temperature sensor is typically located inside the Frame sill (bottom) towards the left side.

Figure K.1: 4-Door Frame Layout Example for Energy Controller and Sensor Locations




## Programming, Settings, and Parameters

### Sensor Button

Use the Sensor button to set dewpoint offsets to the unit in addition to the 24-hour [gasket](#) seat mode. There are 3 additional modes that the button will go through when it is held (see modes below).

**Figure K.2: Energy Controller (Dew Point Sensor)**



## Settings

### Offset Status Indicator Mode

In addition to the factory setting, there is an option to add additional offset to the Temperature sensor. This mode is used to verify offset setting (in addition to Dew Point temperature + 10°F) the system is currently in. If the button is held for less than 10 seconds, the LED will blink up to 4 times.

- 1 Blink
  - 1 Blink of the LED indicates that there is no offset added to the (Dewpoint Temperature + 10°F) calculation
- 2 Blinks
  - 2 Blinks of the LED indicate that there is a 3°F offset added to the (Dewpoint Temperature + 10°F) calculation. The overall cut off Temperature is (Dew point Temperature + 13°F)
- 3 Blinks
  - 3 Blinks of the LED indicate that there is a 9°F offset added to the (Dewpoint Temperature + 10°F) calculation. The overall cut off Temperature is (Dew point Temperature + 19°F)
- 4 Blinks
  - 4 Blinks of the LED indicate that there is a 18°F offset added to the (Dewpoint Temperature + 10°F) calculation. The overall cut off Temperature is (Dew point Temperature + 28°F)

Releasing the button during this time period will return the unit to normal operation. The first mode is intended to inform the technician if there is an offset being added to the dewpoint calculation.

### 24-Hour Heat Mode

This mode is used to turn 24-hour constant heat on Frame/Door System, this mode will keep the heat on for a continuous 24-hour period and then revert to the previous setting. When the unit is in a 24-hour heat mode, the LED will blink slowly with an interval of 1 second to indicate that the heater is on for the remainder of the 24-hour heat mode. To set hold down the button for longer than 10 seconds but less than 20 seconds, the 24-hour heat mode is displayed by flashing the LED slowly. If the button is released during this time, the unit will either enter the 24-hour heat mode if it is not in it already or leave it if it is already in this mode.

### Offset Setting Options

When the sensor button is held for longer than 20 seconds, the LED will flash once, twice, three times, or four times in Five Second Intervals. The blink represents the Temperature offset point in addition to Cut off Temperature (Dew Point Temperature + 10°F).

- 1 Blink ( 1/2 Second Blink. No Blink for 4 1/2 Seconds)
  - No offset (The overall cut off Temperature is (Dew point Temperature + 10°F))
- 2 Blinks (Blinks for 1 Second. No Blinks for 4 Seconds)
  - 3°F offset (The overall cut off Temperature is (Dew point Temperature + 13°F))
- 3 Blinks (Blinks for 1 1/2 Seconds. No Blinks for 3 1/2 Seconds)
  - 9°F offset (The overall cut off Temperature is (Dew point Temperature + 19°F))
- 4 Blinks (Blinks for 2 Seconds. No Blinks for 3 Seconds)
  - 18°F offset (The overall cut off Temperature is (Dew point Temperature + 28°F))

Release the sensor button when the desired dewpoint offset flash is displayed via the LED. The technician then can check the setpoint by entering the Offset Status Indicator Mode, as previously described.

## Troubleshooting

- When the unit is operating normally, the LED of the sensor will display the status of the heater.
- When the heater is off, the LED will blink very dimly to show that the unit is operating, but the heater is off.
- When the heater is on, the LED will be illuminated constantly.
- Sensor Disconnect - If at any time during normal operation a sensor is disconnected, via a cut wire or fully disconnected the sensor, the LED will blink quickly, and the heater will be on to ensure the glass does not sweat.

## Replacement Part Numbers

The following table is a list of replacement part numbers for your Anthony Energy Controller.

Replacement Part Number	Description	Quantity
<a href="#">60-22715-0002</a>	AEC Energy Controller Assembly	1 per Frame Section
40-25072-1005	Screws for AEC Energy Controller	2 per Frame Section
<a href="#">40-12665-3003</a>	Screws to install Humidity Sensor	2 per Frame Section
<a href="#">40-12665-3003</a>	Screw to Install Temperature Sensor	1 per Frame Section
20-24817-0001 20-24817-0002	Humidity Sensor Cover	1 each per Frame Section

## Replacement Instructions

The following instructions will guide you on how to replace an Anthony Energy Controller.

1. Locate the Mullion with LED Light Switch and remove the contact plate by disengaging the zipper strips.
2. Locate the Energy Controller and unscrew the Controller.
3. Locate the Temperature sensor located on the Frame sill towards the left side. Remove the contact plate and unscrew the sensor
4. Also, unscrew the Humidity Sensor from the Frame header.
5. Replace the Energy Controller and screw the Temperature Sensor and Humidity Sensor.
6. Check if the newly replaced Energy controller is working. (refer to the troubleshooting instructions)
7. Put back the Mullion and Sill contact plates by engaging zipper strips. (If needed use new Zipper Strips).





## Revision History

REV	ORIGINATOR	DESCRIPTION OF CHANGE	DATE
A	A. Martinez / E. Chavez	Initial Release. See ECN 18672	9/15/2022
B	HOLST	Update Locations ECN19361	9/6/2023