



NOTES:

- A. ALL WIRING SHALL BE 14 AWG TYPE THIN-THIN-AWM, RATED 600V, 105 C.
- B. ALL WIRING SHALL CONFORM TO THE NATIONAL AND CANADIAN ELECTRIC CODE
- C. FREEZER TEMPERATURE SHALL MAINTAIN -10° TO 0° F
- D. MULLION HEATER UL/CSA LISTED 'HEAT TECH , INC., 88" LG. DOUBLE SERIES HEATER CABLE RATED AT 115 VOLT, 3 D WATT PER FOOT, W/2-48" LEADS HETEAR TAPE LEADS
 PRIMARY CIRCUIT - BLACK AND WHITE
 SECONDARY CIRCUIT - BLUE AND YELLOW
 (CAPOFF SECONDARY LEADS)
- E. EVAPORATOR - 3/8" O.D. COPPER TUBING, DOLD WALL CONSTRUCTION, APPROXIMATELY 408" LONG.
- F. CONDENSING UNIT IS UL LISTED - RATED AT 1/3 HP, 115 VOLT, 60HZ, 1PH, 404A REFRIGERANT

ITEM	PART NO.	QTY	DESCRIPTION
11	E-1-19-1	1	SWITCH, CARLING, LIGHT ROCKER #LTA-201-TRB
10	E-2-12	1	J- BOX, 2 X 4 X 2
9	E-2-3-1	1	PLATE, 2 X 4 GALV COVER
8	P-1-207	1	COMPRESSOR, COPELAND #M4YL-0035-1AA-204, 1/3 HP.
7	E-5-23	2	HEAT CABLE, DOUBLE, 115V, 88" LG.
6	P-1-53-1200	1	CAP TUBE #112, .050 I.D. X .093 O.D., 100" LONG
5	P-1-23	1	DRYER, SPORLAN #C-052-S 1H
4	P-1-18-B	1	THERMOSTAT, CUTLER-HAMMER, #9030N1230
3	P-1-48	1	ACCUMULATOR, 3/8 STRAIGHT, WATSCO #A-B
2	E-4-15	1	THERMOMETER, F-DEG. #RR400 OR #RR100FA-24
1	E-10-12-10	1	CORD, 14/3 SJO 8' LG. W/STRAIGHT PLUG

STORE NO:		ITEM NO:		SHEET:	1 OF 1
CUSTOMER:	H & K Dallas Inc.	TITLE:	ASSEMBLY.	DATE:	01/MAR/02
ASSEMBLY TEMPLATE B	DALLAS TEXAS	DRAWN:	EMPLOYEE NAME	SYN:	-
THESE DIMENSIONS AND SPECIFICATIONS ARE THE PROPERTY OF H&K AND SHALL NOT BE REPRODUCED OR GIVEN OR PASSED ON TO A THIRD PARTY WITHOUT THE WRITTEN PERMISSION OF H&K.	CHECKED:	REVISION:	-	DATE:	-
DRAWING NO:	H & K Dallas Inc.	SOLD:	NONE	DATE:	-



